

---

**nose2**

***Release 0.15.1***

**Author name not set**

**Oct 11, 2024**



# CONTENTS

<b>1</b>	<b>nose2 vs nose</b>	<b>3</b>
<b>2</b>	<b>nose2 vs pytest</b>	<b>5</b>
<b>3</b>	<b>Quickstart</b>	<b>7</b>
<b>4</b>	<b>Full Docs</b>	<b>9</b>
<b>5</b>	<b>Versions and Support</b>	<b>11</b>
5.1	Changelog and Version Scheme . . . . .	11
5.2	Python Versions . . . . .	11
<b>6</b>	<b>Contributing</b>	<b>13</b>
<b>7</b>	<b>User's Guide</b>	<b>15</b>
7.1	Getting started with nose2 . . . . .	15
7.2	Using nose2 . . . . .	15
7.3	Configuring nose2 . . . . .	18
7.4	Differences: nose2 vs nose vs unittest2 . . . . .	21
7.5	Plugins for nose2 . . . . .	22
7.6	Tools and Helpers . . . . .	67
7.7	Changelog . . . . .	76
<b>8</b>	<b>Plugin Developer's Guide</b>	<b>87</b>
8.1	Writing Plugins . . . . .	87
8.2	Documenting plugins . . . . .	90
8.3	Event reference . . . . .	90
8.4	Hook reference . . . . .	98
8.5	Session reference . . . . .	105
8.6	Plugin class reference . . . . .	107
<b>9</b>	<b>Developer's Guide</b>	<b>111</b>
9.1	Contributing to nose2 . . . . .	111
9.2	Internals . . . . .	112
<b>10</b>	<b>Indices and tables</b>	<b>119</b>
	<b>Python Module Index</b>	<b>121</b>
	<b>Index</b>	<b>123</b>



nose2's extends `unittest` to make testing nicer.



## NOSE2 VS NOSE

`nose2` originated as the successor to `nose`.

`nose2` is a distinct project and does not support all of the behaviors of `nose`. See [differences](#) for a thorough rundown.





## NOSE2 VS PYTEST

`pytest` is an excellent test framework and we encourage users to consider it for new projects. It has a bigger team of maintainers and a larger community of users.



## QUICKSTART

Because `nose2` is based on `unittest`, you can start from the Python Standard Library's [documentation for `unittest`](#) and then use `nose2` to add value on top of that.

`nose2` looks for tests in Python files whose names start with `test` and runs every test function it discovers.

Here's an example of a simple test, written in typical `unittest` style:

```
# in test_simple.py
import unittest

class TestStrings(unittest.TestCase):
    def test_upper(self):
        self.assertEqual("spam".upper(), "SPAM")
```

You can then run this test like so:

```
$ nose2 -v
test_upper (test_simple.TestStrings) ... ok

-----
Ran 1 test in 0.000s

OK
```

However, `nose2` supports more testing configuration and provides more tools than `unittest` on its own.

For example, this test exercises just a few of `nose2`'s features:

```
# in test_fancy.py
from nose2.tools import params

@params("Sir Bedevere", "Miss Islington", "Duck")
def test_is_knight(value):
    assert value.startswith('Sir')
```

and then run this like so:

```
$ nose2 -v --pretty-assert
test_fancy.test_is_knight:1
'Sir Bedevere' ... ok
test_fancy.test_is_knight:2
'Miss Islington' ... FAIL
test_fancy.test_is_knight:3
```

(continues on next page)

(continued from previous page)

```
'Duck' ... FAIL

=====
FAIL: test_fancy.test_is_knight:2
'Miss Islington'
-----
Traceback (most recent call last):
  File "/mnt/ebs/home/sirosen/tmp/test_fancy.py", line 6, in test_is_knight
    assert value.startswith('Sir')
AssertionError

>>> assert value.startswith('Sir')

values:
  value = 'Miss Islington'
  value.startswith = <built-in method startswith of str object at 0x7f3c3172f430>
=====
FAIL: test_fancy.test_is_knight:3
'Duck'
-----
Traceback (most recent call last):
  File "/mnt/ebs/home/sirosen/tmp/test_fancy.py", line 6, in test_is_knight
    assert value.startswith('Sir')
AssertionError

>>> assert value.startswith('Sir')

values:
  value = 'Duck'
  value.startswith = <built-in method startswith of str object at 0x7f3c3172d490>
-----
Ran 3 tests in 0.001s

FAILED (failures=2)
```

**FULL DOCS**

Full documentation for nose2 is available at [docs.nose2.io](https://docs.nose2.io)



## VERSIONS AND SUPPORT

### 5.1 Changelog and Version Scheme

nose2 versions are numbered `0.MAJOR.MINOR`. Minor releases contain bugfixes or smaller features. Major features or backwards incompatible changes are done in major releases.

For a full description of all past versions and changes, see the [changelog](#).

### 5.2 Python Versions

nose2 requires Python 3.

It supports all versions currently supported by the CPython team, and also aims to support PyPy and cpython betas.

#### 5.2.1 Python 2

Python 2 is no longer supported. The [0.12.x line of releases](#) contains the last versions which supported Python 2.

Users of Python 2 should understand that Python 2 is EOL and the Python 2 support line for nose2 is similarly considered EOL.

#### Note

Fixes to 0.12.x may still be accepted on an as-needed basis for a short while as the python3-only line of releases gets started.





## CONTRIBUTING

If you want to make contributions, please read the [contributing](#) guide.



## 7.1 Getting started with nose2

### 7.1.1 Installation

The recommended way to install nose2 is with `pip`

```
pip install nose2
```

### 7.1.2 Running tests

To run tests in a project, use the `nose2` script that is installed with nose2:

```
nose2
```

This will find and run tests in all packages in the current working directory, and any sub-directories of the current working directory whose names start with 'test'.

To find tests, nose2 looks for modules whose names start with 'test'. In those modules, nose2 will load tests from all `unittest.TestCase` subclasses, as well as functions whose names start with 'test'.

The `nose2` script supports a number of command-line options, as well as extensive configuration via config files. For more information see [Using nose2](#) and [Configuring nose2](#).

## 7.2 Using nose2

### 7.2.1 Naming Tests

nose2 will look in each directory under the starting directory, unless the configuration modifies the included paths. Within directories and within any Python packages found in the starting directory and any source directories in the starting directory, nose2 will discover test modules and load tests from them. "Test modules" means any modules whose names start with "test". See the Configuration section for ways to modify searching for tests.

Directories nose2 will look in:

- Directory that contains an `__init__.py` file (a Python package)
- Directory name that contains "test" after being lowercased.
- Directory name that is either `lib` or `src`

Each of the following test files will be run:

```
test.py
test_views.py
test_models.py
testThingy.py
```

These files will not be run:

```
not_a_test.py
myapp_test.py
some_test_file.py
```

Within test modules, nose2 will load tests from `unittest.TestCase` subclasses, and from test functions (functions whose names begin with “test”).

## 7.2.2 Running Tests

In the simplest case, go to the directory that includes your project source and run nose2 there:

```
nose2
```

This will discover tests in packages and test directories under that directory, load them, and run them, then output something like:

```
.....
-----
Ran 77 tests in 1.897s

OK
```

To change the place discovery starts, or to change the top-level importable directory of the project, use the `-s` and `-t` options.

**-s** START\_DIR, **--start-dir** START\_DIR

Directory to start discovery. Defaults to the current working directory. This directory is where nose2 will start looking for tests.

**-t** TOP\_LEVEL\_DIRECTORY, **--top-level-directory** TOP\_LEVEL\_DIRECTORY,  
**--project-directory** TOP\_LEVEL\_DIRECTORY

Top-level directory of the project. Defaults to the starting directory. This is the directory containing importable modules and packages, and is always prepended to `sys.path` before test discovery begins.

## Specifying Tests to Run

Pass *test names* to nose2 on the command line to run individual test modules, classes, or tests.

A test name consists of a *python object part* and, for generator or parameterized tests, an *argument part*. The *python object part* is a dotted name, such as `pkg1.tests.test_things.SomeTests.test_ok`. The argument part is separated from the python object part by a colon (“:”) and specifies the *index* of the generated test to select, *starting from 1*. For example, `pkg1.test.test_things.test_params_func:1` would select the *first* test generated from the parameterized test `test_params_func`.

Plugins may provide other means of test selection.

## Running Tests with `python setup.py test`

nose2 supports distribute/setuptools' `python setup.py test` standard for running tests. To use nose2 to run your package's tests, add the following to your `setup.py`:

```
setup(...
    test_suite='nose2.collector.collector',
    ...
)
```

(Not literally. Don't put the '...' parts in.)

Two warnings about running tests this way.

One: because the setuptools test command is limited, nose2 returns a "test suite" that actually takes over the test running process completely, bypassing the test result and test runner that call it. This may be incompatible with some packages.

Two: because the command line arguments to the test command may not match up properly with nose2's arguments, the nose2 instance started by the collector *does not accept any command line arguments*. This means that it always runs all tests, and that you cannot configure plugins on the command line when running tests this way. As a workaround, when running under the test command, nose2 will read configuration from `setup.cfg` if it is present, in addition to `unittest.cfg` and `nose2.cfg`. This enables you to put configuration specific to the setuptools test command in `setup.cfg` – for instance to activate plugins that you would otherwise activate via the command line.

## 7.2.3 Getting Help

Run:

```
nose2 -h
```

to get help for nose2 itself and all loaded plugins.

```
usage: nose2 [-s START_DIR] [-t TOP_LEVEL_DIRECTORY] [--config [CONFIG]]
             [--no-user-config] [--no-plugins] [--verbose] [--quiet] [-B] [-D]
             [--collect-only] [--log-capture] [-P] [-h]
             [testNames [testNames ...]]

positional arguments:
  testNames

optional arguments:
  -s START_DIR, --start-dir START_DIR
                        Directory to start discovery ('.' default)
  -t TOP_LEVEL_DIRECTORY, --top-level-directory TOP_LEVEL_DIRECTORY, --project-directory
  ↪ TOP_LEVEL_DIRECTORY
                        Top level directory of project (defaults to start dir)
  --config [CONFIG], -c [CONFIG]
                        Config files to load, if they exist. ('unittest.cfg'
                        and 'nose2.cfg' in start directory default)
  --no-user-config      Do not load user config files
  --no-plugins          Do not load any plugins. Warning: nose2 does not do
                        anything if no plugins are loaded
  --verbose, -v         Show this help message and exit
  --quiet
  -h, --help
```

(continues on next page)

(continued from previous page)

```

plugin arguments:
  Command-line arguments added by plugins:

  -B, --output-buffer    Enable output buffer
  -D, --debugger          Enter pdb on test fail or error
  --collect-only          Collect but do not run tests. With '-v', this will output test_
↪ names
  --log-capture           Enable log capture
  -P, --print-hooks       Print names of hooks in order of execution

```

## 7.3 Configuring nose2

### 7.3.1 Configuration Files

nose2 can be configured via standard, ini-style config files. The default files are `unittest.cfg` and `nose2.cfg` in the start directory.

The ini format has sections marked off by brackets ("`[unittest]`") and `key = value` pairs within those sections. When the value is a list, put each value into its own line with proper indentation

```

key_expect_list = value1
                  value2

```

Two command line options, `-c` and `--no-user-config` may be used to determine which config files are loaded.

**-c CONFIG, --config CONFIG**

Config files to load. Default behavior is to look for `unittest.cfg` and `nose2.cfg` in the start directory, as well as any user config files (unless `--no-user-config` is selected).

**--no-user-config**

Do not load user config files. If not specified, in addition to the standard config files and any specified with `-c`, nose2 will look for `.unittest.cfg` and `.nose2.cfg` in the user's \$HOME directory.

### Configuring Test Discovery

The `[unittest]` section of nose2 config files is used to configure nose2 itself. The following options are available to configure test discovery:

**start-dir**

This option configures the default directory to start discovery. The default value is `"."` (the current directory where nose2 is executed). This directory is where nose2 will start looking for tests.

**code-directories**

This option configures nose2 to add the named directories to `sys.path` and the discovery path. Use this if your project has code in a location other than the top level of the project, or the directories `lib` or `src`. The value here may be a list: put each directory on its own line in the config file.

**test-file-pattern**

This option configures how nose detects test modules. It is a file glob.

**test-method-prefix**

This option configures how nose detects test functions and methods. The prefix set here will be matched (via simple string matching) against the start of the name of each method in test cases and each function in test modules.

Examples:

```
[unittest]
start-dir = tests
code-directories = source
                  more_source
test-file-pattern = *_test.py
test-method-prefix = t
```

### Specifying Plugins to Load

To avoid loading any plugins, use the `--no-plugins` option. Beware, though: nose2 does all test discovery and loading via plugins, so unless you are patching in a custom test loader and runner, when run with `--no-plugins`, nose2 will do nothing.

#### `--no-plugins`

Do not load any plugins. *This kills the nose2.*

To specify plugins to load beyond the builtin plugins automatically loaded, add a `plugins` entry under the `[unittest]` section in a config file.

#### `plugins`

List of plugins to load. Put one plugin module on each line.

To exclude some plugins that would otherwise be loaded, add an `exclude-plugins` entry under the `[unittest]` section in a config file.

#### `exclude-plugins`

List of plugins to exclude. Put one plugin module on each line.

#### Note

It bears repeating that in both `plugins` and `exclude-plugins` entries, you specify the plugin *module*, not the plugin *class*. The module is specified by the (dot-separated) *fully qualified* name.

Examples:

```
[unittest]
plugins = myproject.plugins.frobulate
         otherproject.contrib.plugins.derper

exclude-plugins = nose2.plugins.loader.functions
                 nose2.plugins.outcomes
```

## 7.3.2 Configuring Plugins

Most plugins specify a config file section that may be used to configure the plugin. If nothing else, any plugin that specifies a config file section can be set to automatically register by including `always-on = True` in its config:

```
[my-plugin]
always-on = True
```

Plugins may accept any number of other config values, which may be booleans, strings, integers or lists. A polite plugin will document these options somewhere. Plugins that want to make use of nose2's `Sphinx` extension as detailed in *Documenting plugins* must extract all of their config values in their `__init__` methods.

### 7.3.3 Test Runner Tips and Tweaks

#### Running Tests in a Single Module

You can use `nose2.main` in the same way that `unittest.main` (and `unittest2.main`) have historically worked: to run the tests in a single module. Just put a block like the following at the end of the module:

```
if __name__ == '__main__':
    import nose2
    nose2.main()
```

Then *run the module directly* – In other words, do not run the `nose2` script.

#### Rolling Your Own Runner

You can take more control over the test runner by foregoing the `nose2` script and rolling your own. To do that, you just need to write a script that calls `nose2.discover`, for instance:

```
if __name__ == '__main__':
    import nose2
    nose2.discover()
```

You can pass several keyword arguments to `nose2.discover`, all of which are detailed in the documentation for [`nose2.main.PluggableTestProgram`](#).

#### Altering the Default Plugin Set

To add plugin *modules* to the list of those automatically loaded, you can pass a list of module names to add (the `plugins`) argument or exclude (`excludePlugins`). You can also subclass [`nose2.main.PluggableTestProgram`](#) and set the class-level `defaultPlugins` and `excludePlugins` attributes to alter plugin loading.

#### When Loading Plugins from Modules is not Enough

**None of which will help** if you need to register a plugin *instance* that you’ve loaded yourself. For that, use the `extraHooks` keyword argument to `nose2.discover`. Here, you pass in a list of 2-tuples, each of which contains a hook name and a plugin *instance* to register for that hook. This allows you to register plugins that need runtime configuration that is not easily passed in through normal channels – and also to register *objects that are not nose2 plugins* as hook targets. Here’s a trivial example:

```
if __name__ == '__main__':
    import nose2

    class Hello(object):
        def startTestRun(self, event):
            print("hello!")

    nose2.discover(extraHooks=[('startTestRun', Hello())])
```

This can come in handy when integrating with other systems that expect you to provide a test runner that they execute, rather than executing tests yourself (django, for instance).



## 7.4 Differences: nose2 vs nose vs unittest2

### 7.4.1 nose2 is not nose

#### What's Different

##### Python Versions

nose supports Python 2.4 and above, but nose2 only supports Python versions currently supported by the Python team.

##### Test Discovery and Loading

nose loads test modules lazily: tests in the first-loaded module are executed before the second module is imported. *nose2 loads all tests first, then begins test execution.* This has some important implications.

First, it means that nose2 does not need a custom importer. nose2 imports test modules with `__import__()`.

Second, it means that *nose2 does not support all of the test project layouts that nose does.* Specifically, projects that look like this will fail to load tests correctly with nose2:

```
.
|-- tests
|   |-- more_tests
|   |   |-- test.py
|   |-- test.py
```

To nose's loader, those two test modules look like different modules. But to nose2's loader, they look the same, and will not load correctly.

##### Test Fixtures

nose2 supports only the *same levels of fixtures as unittest2*. This means class level fixtures and module level fixtures are supported, but *package-level fixtures are not*. In addition, unlike nose, nose2 does not attempt to order tests named on the command-line to group those with the same fixtures together.

##### Parameterized and Generator Tests

nose2 supports *more kinds of parameterized and generator tests than nose*, and supports all test generators in test functions, test classes, and in unittest TestCase subclasses. nose supports them only in test functions and test classes that do not subclass unittest.TestCase. See: [Loader: Test Generators](#) and [Loader: Parameterized Tests](#) for more.

##### Configuration

nose expects plugins to make all of their configuration parameters available as command-line options. *nose2 expects almost all configuration to be done via configuration files.* Plugins should generally have only one command-line option: the option to activate the plugin. Other configuration parameters should be loaded from config files. This allows more repeatable test runs and keeps the set of command-line options small enough for humans to read. See: [Configuring nose2](#) for more.

##### Plugin Loading

nose uses setuptools entry points to find and load plugins. nose2 does not. Instead, *nose2 requires that all plugins be listed in config files.* This ensures that no plugin is loaded into a test system just by virtue of being installed somewhere, and makes it easier to include plugins that are part of the project under test. See: [Configuring nose2](#) for more.

## Limited support for `python setup.py test`

nose2 supports setuptools' `python setup.py test` command, but via very different means than nose. To avoid the internal complexity forced on nose by the fact that the setuptools test command can't be configured with a custom test runner, when run this way, *nose2 essentially hijacks the test running process*. The “test suite” that `nose2.collector.collector()` returns actually *is* a test runner, cloaked inside of a test case. It loads and runs tests as normal, setting up its own test runner and test result, and calls `sys.exit()` itself – completely bypassing the test runner and test result that setuptools/unittest create. This may be incompatible with some projects.

## Plugin API

nose2 implements a new plugin API based on the work done by Michael Foord in unittest2's `plugins` branch. This API is greatly superior to the one in nose, especially in how it allows plugins to interact with each other. But it is different enough from the API in nose that supporting nose plugins in nose2 is not practical: *plugins must be rewritten to work with nose2*. See: *Writing Plugins* for more.

## Missing Plugins

*nose2 does not include some of the more commonly-used plugins in nose*. Some of nose's builtin plugins could not be ported to nose2 due to differences in internals. See: *Plugins for nose2* for information on the plugins built in to nose2.

## Internals

nose wraps or replaces everything in unittest. nose2 does a bit less: *it does not wrap TestCases*, and does not wrap the test result class with a result proxy. nose2 does subclass `TestProgram`, and install its own loader, runner, and result classes. It does this unconditionally, rather than allowing arguments to `TestProgram.__init__()` to specify the test loader and runner. See *Internals* for more information.

## License

While nose was LGPL, nose2 is BSD licensed. This change was made at the request of the majority of nose contributors.

## What's the Same

### Philosophy

nose2 has the same goals as nose: to extend unittest to make testing nicer and easier to understand. It aims to give developers flexibility, power and transparency, so that common test scenarios require no extra work, and uncommon test scenarios can be supported with minimal fuss and magic.

## 7.4.2 nose2 is not (exactly) unittest2/plugins

nose2 is based on the unittest2 `plugins` branch, but differs from it in several substantial ways. The *event api not exactly the same* because nose2 can't replace `unittest.TestCase`, and *does not configure the test run or plugin set globally*. nose2 also has a *wholly different reporting API* from unittest2's plugins, to better support some common cases (like adding extra information to error output). nose2 also *defers more work to plugins* than unittest2: the test loader, runner and result are just plugin callers, and all of the logic of test discovery, running and reporting is implemented in plugins. This means that unlike unittest2, *nose2 includes a substantial set of plugins that are active by default*.

## 7.5 Plugins for nose2

### 7.5.1 Built in and Loaded by Default

These plugins are loaded by default. To exclude one of these plugins from loading, add the plugin's fully qualified module name to the `exclude-plugins` list in a config file's `[unittest]` section, or pass the plugin module with

the `--exclude-plugin` argument on the command line. You can also pass plugin module names to exclude to a `nose2.main.PluggableTestProgram` using the `excludePlugins` keyword argument.

### Loader: Test discovery

Discovery-based test loader.

This plugin implements nose2's automatic test module discovery. It looks for test modules in packages and directories whose names start with `test`, then fires the `loadTestsFromModule()` hook for each one to allow other plugins to load the actual tests.

It also fires `handleFile()` for every file that it sees, and `matchPath()` for every Python module, to allow other plugins to load tests from other kinds of files and to influence which modules are examined for tests.

### Configuration [discovery]

**always-on**

**Default**

True

**Type**

boolean

### Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[discovery]
always-on = True
```

### Plugin class reference: DiscoveryLoader

**class** `nose2.plugins.loader.discovery.DiscoveryLoader(*args, **kwargs)`

Loader plugin that can discover tests

**loadTestsFromName(event)**

Load tests from module named by event.name

**loadTestsFromNames(event)**

Discover tests if no test names specified

### Loader: Test Functions

Load tests from test functions in modules.

This plugin responds to `loadTestsFromModule()` by adding test cases for all test functions in the module to `event.extraTests`. It uses `session.testMethodPrefix` to find test functions.

Functions that are generators, have param lists, or take arguments are not collected.

This plugin also implements `loadTestsFromName()` to enable loading tests from dotted function names passed on the command line.

## Fixtures

Test functions can specify setup and teardown fixtures as attributes on the function, for example:

```
x = 0

def test():
    assert x

def setup():
    global x
    x = 1

def teardown():
    global x
    x = 1

test.setup = setup
test.teardown = teardown
```

The setup attribute may be named `setup`, `setUp` or `setUpFunc`. The teardown attribute may be named `teardown`, `tearDown` or `tearDownFunc`.

## Other attributes

The other significant attribute that may be set on a test function is `paramList`. When `paramList` is set, the function will be collected by the *parameterized test loader*. The easiest way to set `paramList` is with the `nose2.tools.params()` decorator.

## Configuration [functions]

### always-on

<b>Default</b>
True
<b>Type</b>
boolean

### Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[functions]
always-on = True
```

## Plugin class reference: Functions

**class** nose2.plugins.loader.functions.**Functions**(\*args, \*\*kwargs)

Loader plugin that loads test functions

**loadTestsFromModule**(event)

Load test functions from event.module

**loadTestsFromName**(event)

Load test if event.name is the name of a test function

## Loader: Test Generators

Load tests from generators.

This plugin implements `loadTestFromTestCase()`, `loadTestsFromName()` and `loadTestFromModule()` to enable loading tests from generators.

Generators may be functions or methods in test cases. In either case, they must yield a callable and arguments for that callable once for each test they generate. The callable and arguments may all be in one tuple, or the arguments may be grouped into a separate tuple:

```
def test_gen():
    yield check, 1, 2
    yield check, (1, 2)
```

To address a particular generated test via a command-line test name, append a colon (':') followed by the index (*starting from 1*) of the generated case you want to execute.

## Configuration [generators]

### always-on

**Default**  
True

**Type**  
boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[generators]
always-on = True
```

## Plugin class reference: Generators

**class** nose2.plugins.loader.generators.**Generators**(\*args, \*\*kwargs)

Loader plugin that loads generator tests

**getTestCaseNames**(event)

Get generator test case names from test case class

**loadTestsFromModule**(event)

Load tests from generator functions in a module

**loadTestsFromName**(event)

Load tests from generator named on command line

**loadTestsFromTestCase**(event)

Load generator tests from test case

## Loader: Parameterized Tests

Load tests from parameterized functions and methods.

This plugin implements `getTestCaseNames()`, `loadTestsFromModule()`, and `loadTestsFromName()` to support loading tests from parameterized test functions and methods.

To parameterize a function or test case method, use `nose2.tools.params()`.

To address a particular parameterized test via a command-line test name, append a colon (':') followed by the index (*starting from 1*) of the case you want to execute.

## Such And The Parameters Plugin

The parameters plugin can work with the Such DSL, as long as the first argument of the test function is the “case” argument, followed by the other parameters:

```
from nose2.tools import such
from nose2.tools.params import params

with such.A('foo') as it:
    @it.should('do bar')
    @params(1,2,3)
    def test(case, bar):
        case.assertTrue(isinstance(bar, int))

    @it.should('do bar and extra')
    @params((1, 2), (3, 4), (5, 6))
    def testExtraArg(case, bar, foo):
        case.assertTrue(isinstance(bar, int))
        case.assertTrue(isinstance(foo, int))

it.createTests(globals())
```

## Configuration [parameters]

always-on

**Default**

True

**Type**

boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[parameters]
always-on = True
```

## Plugin class reference: Parameters

**class** nose2.plugins.loader.parameters.Parameters(\*args, \*\*kwargs)

Loader plugin that loads parameterized tests

**getTestCaseNames**(event)

Generate test case names for all parameterized methods

**loadTestsFromModule**(event)

Load tests from parameterized test functions in the module

**loadTestsFromName(event)**

Load parameterized test named on command line

**Loader: Test Cases**

Load tests from `unittest.TestCase` subclasses.

This plugin implements `loadTestsFromName()` and `loadTestsFromModule()` to load tests from `unittest.TestCase` subclasses found in modules or named on the command line.

**Configuration [testcases]****always-on****Default**

True

**Type**

boolean

**Sample configuration**

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[testcases]
always-on = True
```

**Plugin class reference: TestCaseLoader**

**class** `nose2.plugins.loader.testcases.TestCaseLoader(*args, **kwargs)`

Loader plugin that loads from test cases

**loadTestsFromModule(event)**

Load tests in `unittest.TestCase` subclasses

**loadTestsFromName(event)**

Load tests from `event.name` if it names a test case/method

**Loader: Test Classes**

Load tests from classes that are *not* `unittest.TestCase` subclasses.

This plugin responds to `loadTestsFromModule()` by adding test cases for test methods found in classes in the module that are *not* subclasses of `unittest.TestCase`, but whose names (lowercased) match the configured test method prefix.

Test class methods that are generators or have param lists are not loaded here, but by the `nose2.plugins.loader.generators.Generators` and `nose2.plugins.loader.parameters.Parameters` plugins.

This plugin also implements `loadTestsFromName()` to enable loading tests from dotted class and method names passed on the command line.

This plugin makes two additional plugin hooks available for other test loaders to use:

`nose2.plugins.loader.testclasses.loadTestsFromTestClass(self, event)`

**Parameters**

**event** – A `LoadFromTestClassEvent` instance

Plugins can use this hook to load tests from a class that is not a `unittest.TestCase` subclass. To prevent other plugins from loading tests from the test class, set `event.handled` to `True` and return a test suite. Plugins can also append tests to `event.extraTests`. Usually, that's what you want, since it allows other plugins to load their tests from the test case as well.

`nose2.plugins.loader.testclasses.getTestMethodNames(self, event)`

#### Parameters

**event** – A `GetTestMethodNamesEvent` instance

Plugins can use this hook to limit or extend the list of test case names that will be loaded from a class that is not a `unittest.TestCase` subclass by the standard nose2 test loader plugins (and other plugins that respect the results of the hook). To force a specific list of names, set `event.handled` to `True` and return a list: this exact list will be the only test case names loaded from the test case. Plugins can also extend the list of names by appending test names to `event.extraNames`, and exclude names by appending test names to `event.excludedNames`.

## About Test Classes

Test classes are classes that look test-like but are not subclasses of `unittest.TestCase`. Test classes support all of the same test types and fixtures as test cases.

To “look test-like” a class must have a name that, lowercased, matches the configured test method prefix – “test” by default. Test classes must also be able to be instantiated without arguments.

What are they useful for? Mostly the case where a test class can't for some reason subclass `unittest.TestCase`. Otherwise, test class tests and test cases are functionally equivalent in nose2, and test cases have broader support and all of those helpful `assert*` methods – so when in doubt, you should use a `unittest.TestCase`.

Here's an example of a test class:

```
class TestSomething(object):  
  
    def test(self):  
        assert self.something(), "Something failed!"
```

## Configuration [test-classes]

### always-on

#### Default

`True`

#### Type

`boolean`

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[test-classes]  
always-on = True
```

## Plugin class reference: TestClassLoader

`class nose2.plugins.loader.testclasses.TestClassLoader(*args, **kwargs)`

Loader plugin that loads test functions



**loadTestsFromModule(*event*)**

Load test classes from event.module

**loadTestsFromName(*event*)**

Load tests from event.name if it names a test class/method

**register()**

Install extra hooks

Adds the new plugin hooks:

- loadTestsFromTestClass
- getTestMethodNames

**Loader: load\_tests protocol**

Loader that implements the load\_tests protocol.

This plugin implements the load\_tests protocol as detailed in the documentation for unittest2.

See the [load\\_tests protocol](#) documentation for more information.

**Warning**

Test suites using the load\_tests protocol do not work correctly with the multiprocessing plugin as of nose2 04. This will be fixed in a future release.

**Configuration [load\_tests]****always-on****Default**

True

**Type**

boolean

**Sample configuration**

The default configuration is equivalent to including the following in a unittest.cfg file.

```
[load_tests]
always-on = True
```

**Plugin class reference: LoadTestsLoader**

**class** nose2.plugins.loader.loadtests.**LoadTestsLoader**(\*args, \*\*kwargs)

Loader plugin that implements load\_tests.

**handleDir(*event*)**

Run load\_tests in packages.

If a package itself matches the test file pattern, run load\_tests in its \_\_init\_\_.py, and stop default test discovery for that package.

**moduleLoadedSuite**(*event*)

Run `load_tests` in a module.

May add to or filter tests loaded in module.

### Default filter: `__test__`

This plugin implements `startTestRun()`, which excludes all test objects that define a `__test__` attribute that evaluates to `False`.

### Plugin class reference: `DunderTestFilter`

**class** `nose2.plugins.dundertest.DunderTestFilter(*args, **kwargs)`

Exclude all tests defining a `__test__` attribute that evaluates to `False`.

**startTestRun**(*event*)

Recurse `event.suite` and remove all test suites and test cases that define a `__test__` attribute that evaluates to `False`.

### Reporting test results

Collect and report test results.

This plugin implements the primary user interface for nose2. It collects test outcomes and reports on them to the console, as well as firing several hooks for other plugins to do their own reporting.

To see this report, nose2 MUST be run with the `verbose` flag:

```
nose2 --verbose
```

This plugin extends standard unittest console reporting slightly by allowing custom report categories. To put events into a custom reporting category, change the `event.outcome` to whatever you want. Note, however, that customer categories are *not* treated as errors or failures for the purposes of determining whether a test run has succeeded.

Don't disable this plugin, unless you (a) have another one doing the same job, or (b) really don't want any test results (and want all test runs to `exit(1)`).

### Configuration [test-result]

#### **always-on**

**Default**

True

**Type**

boolean

#### **descriptions**

**Default**

True

**Type**

boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[test-result]
always-on = True
descriptions = True
```

## Plugin class reference: ResultReporter

**class** nose2.plugins.result.ResultReporter(\*args, \*\*kwargs)

Result plugin that implements standard unittest console reporting

**afterTestRun**(event)

Handle afterTestRun hook

- prints error lists
- prints summary
- fires summary reporting hooks (*beforeErrorList()*, *beforeSummaryReport()*, etc)

**startTest**(event)

Handle startTest hook

- prints test description if verbosity > 1

**testOutcome**(event)

Handle testOutcome hook

- records test outcome in reportCategories
- prints test outcome label
- fires reporting hooks (*reportSuccess()*, *reportFailure()*, etc)

## Buffering test output

Buffer stdout and/or stderr during test execution, appending any output to the error reports of failed tests.

This allows you to use print for debugging in tests without making your test runs noisy.

This plugin implements *startTest()*, *stopTest()*, *setTestOutcome()*, *outcomeDetail()*, *beforeInteraction()* and *afterInteraction()* to manage capturing sys.stdout and/or sys.stderr into buffers, attaching the buffered output to test error report detail, and getting out of the way when other plugins want to talk to the user.

## Configuration [output-buffer]

**always-on**

**Default**

False

**Type**

boolean

**stderr**

**Default**

False

**Type**  
boolean

**stdout**

**Default**  
True

**Type**  
boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[output-buffer]
always-on = False
stderr = False
stdout = True
```

## Command-line options

**-B** DEFAULT, **--output-buffer** DEFAULT  
Enable output buffer

## Plugin class reference: `OutputBufferPlugin`

**class** nose2.plugins.buffer.`OutputBufferPlugin`(\*args, \*\*kwargs)

Buffer output during test execution

**afterInteraction**(event)

Start buffering again (does not clear buffers)

**beforeInteraction**(event)

Stop buffering so users can see stdout

**outcomeDetail**(event)

Add buffered output to event.extraDetail

**setTestOutcome**(event)

Attach buffer(s) to event.metadata

**startTest**(event)

Start buffering selected stream(s)

**stopTest**(event)

Stop buffering

## Dropping Into the Debugger

Start a `pdb.post_mortem()` on errors and failures.

This plugin implements `testOutcome()` and will drop into `pdb` whenever it sees a test outcome that includes `exc_info`.

It fires `beforeInteraction()` before launching `pdb` and `afterInteraction()` after. Other plugins may implement `beforeInteraction()` to return `False` and set `event.handled` to prevent this plugin from launching `pdb`.

## Configuration [debugger]

### always-on

#### Default

False

#### Type

boolean

### errors-only

#### Default

False

#### Type

boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[debugger]
always-on = False
errors-only = False
```

## Command-line options

**-D** DEFAULT, **--debugger** DEFAULT

Enter pdb on test fail or error

## Plugin class reference: Debugger

**class** nose2.plugins.debugger.**Debugger**(\*args, \*\*kwargs)

Enter pdb on test error or failure

### **pdb**

For ease of mocking and using different pdb implementations, pdb is aliased as a class attribute.

**pdb** = <module 'pdb' from '/usr/lib64/python3.13/pdb.py'>

**testOutcome**(event)

Drop into pdb on unexpected errors or failures

## Stopping After the First Error or Failure

Stop the test run after the first error or failure.

This plugin implements `testOutcome()` and sets `event.result.shouldStop` if it sees an outcome with `exc_info` that is not expected.

## Command-line options

**-F** DEFAULT, **--fail-fast** DEFAULT

Stop the test run after the first error or failure

### Plugin class reference: FailFast

**class** nose2.plugins.failfast.**FailFast**(\*args, \*\*kwargs)

Stop the test run after error or failure

**resultCreated**(event)

Mark new result

**testOutcome**(event)

Stop on unexpected error or failure

### Capturing log messages

Capture log messages during test execution, appending them to the error reports of failed tests.

This plugin implements `startTestRun()`, `startTest()`, `stopTest()`, `setTestOutcome()`, and `outcomeDetail()` to set up a logging configuration that captures log messages during test execution, and appends them to error reports for tests that fail or raise exceptions.

### Configuration [log-capture]

#### **always-on**

**Default**

False

**Type**

boolean

#### **clear-handlers**

**Default**

False

**Type**

boolean

#### **date-format**

**Default**

None

**Type**

str

#### **filter**

**Default**

['-nose']

**Type**

list

#### **format**

**Default**

%(name)s: %(levelname)s: %(message)s

**Type**

str

**log-level**

**Default**  
NOTSET

**Type**  
str

**Sample configuration**

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[log-capture]
always-on = False
clear-handlers = False
filter = -nose
format = %(name)s: %(levelname)s: %(message)s
log-level = NOTSET
```

**Command-line options**

**--log-capture** DEFAULT  
Enable log capture

**Plugin class reference: LogCapture**

**class** nose2.plugins.logcapture.**LogCapture**(\*args, \*\*kwargs)

Capture log messages during test execution

**outcomeDetail**(event)  
Append captured log messages to event.extraDetail

**setTestOutcome**(event)  
Store captured log messages in event.metadata

**startTest**(event)  
Set up handler for new test

**startTestRun**(event)  
Set up logging handler

**stopTest**(event)  
Clear captured messages, ready for next test

**Test coverage reporting**

Use this plugin to activate coverage report.

To use this plugin, you need to install nose2[coverage\_plugin]. e.g.

```
$ pip install nose2[coverage_plugin]>=0.6.5
```

Then, you can enable coverage reporting with :

```
$ nose2 --with-coverage
```

Or with this lines in `unittest.cfg` :

```
[coverage]
always-on = True
```

You can further specify coverage behaviors with a `.coveragerc` file, as specified by [Coverage Config](#). However, when doing so you should also be aware of *Differences From coverage*.

## Configuration [coverage]

### always-on

**Default**  
False

**Type**  
boolean

### coverage

**Default**  
[]

**Type**  
list

### coverage-combine

**Default**  
False

**Type**  
boolean

### coverage-config

**Default**  
**Type**  
str

### coverage-report

**Default**  
[]

**Type**  
list

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[coverage]
always-on = False
coverage =
coverage-combine = False
coverage-config =
coverage-report =
```



## Command-line options

**--coverage** PATH

Measure coverage for filesystem path (multi-allowed)

**--coverage-report** TYPE

Generate selected reports, available types: term, term-missing, annotate, html, xml (multi-allowed)

**--coverage-config** FILE

Config file for coverage, default: .coveragerc

**-C** DEFAULT, **--with-coverage** DEFAULT

Turn on coverage reporting

## Plugin class reference: Coverage

**class** nose2.plugins.coverage.Coverage(\*args, \*\*kwargs)

**afterSummaryReport**(event)

Reporting data is collected, failure status determined and set. Now print any buffered error output saved from beforeSummaryReport

**beforeSummaryReport**(event)

Only called if active so stop coverage and produce reports.

**createTests**(event)

Start coverage early to catch imported modules.

Only called if active so, safe to just start without checking flags

**handleArgs**(event)

Get our options in order command line, config file, hard coded.

**wasSuccessful**(event)

Mark full test run as successful or unsuccessful

## Differences From coverage

The coverage tool is the basis for nose2's coverage reporting. nose2 will seek to emulate coverage behavior whenever possible, but there are known cases where this is not feasible.

If you need the exact behaviors of coverage, consider having coverage invoke nose2.

Otherwise, please be aware of the following known differences:

- The fail\_under parameter results in an exit status of 2 for coverage, but an exit status of 1 for nose2

## Compatibility with mp plugin

The coverage and mp plugins may be used in conjunction to enable multiprocess testing with coverage reporting.

Special instructions:

- Due to the way the plugin is reloaded in subprocesses, command-line options for the coverage plugin have no effect. If you need to change any coverage plugin options, use a configuration file.
- Do *not* use the concurrency option within a .coveragerc file ; this interferes with the coverage plugin, which automatically handles multiprocess coverage reporting.

## Use assert statements in tests

Make assert statements print pretty output, including source.

This makes `assert x == y` more usable, as an alternative to `self.assertEqual(x, y)`

This plugin implements `outcomeDetail()` and checks for `event.exc_info`. If it finds that an `AssertionError` happened, it will inspect the traceback and add additional detail to the error report.

## Configuration [pretty-assert]

### always-on

#### Default

False

#### Type

boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[pretty-assert]
always-on = False
```

## Command-line options

**--pretty-assert** DEFAULT

Add pretty output for “assert” statements

## Plugin class reference: PrettyAssert

**class** nose2.plugins.prettyassert.**PrettyAssert**(\*args, \*\*kwargs)

Add pretty output for “assert” statements

**static** **addAssertDetail**(extraDetail, exc, trace)

Add details to output regarding `AssertionError` and its context

extraDetail: a list of lines which will be joined with newlines and added to the output for this test failure – defined as part of the event format

exc: the `AssertionError` exception which was thrown

trace: a traceback object for the exception

## assert statement inspection

The prettyassert plugin works by inspecting the stack frame which raised an `AssertionError`. Unlike `pytest`’s assertion rewriting code, it does not modify the built-in `AssertionError`.

As a result, it is somewhat limited in its capabilities – it can only report the *bound* values from that stack frame. That means that this type of statement works well:

```
x = f()
y = g()
assert x == y
```

but this type of statement does not:

```
assert f() == g()
```

It will still run, but the prettyassert will tell you that *f* and *g* are functions, not what they evaluated to. This is probably not what you want.

### attribute resolution

The assertion inspection will resolve attributes, so that expressions like this will work as well:

```
assert x.foo == 1
```

But note that the attribute *x.foo* will be resolved *twice* in this case, if the assertion fails. Once when the assertion is evaluated, and again when it is inspected.

As a result, properties with dynamic values may not behave as expected under prettyassert inspection.

## 7.5.2 Built in but *not* Loaded by Default

These plugins are available as part of the nose2 package but *are not loaded by default*. To load one of these plugins, add the plugin module name (as dot-separated, fully qualified name) to the `plugins` list in a config file's `[unittest]` section, or pass the plugin module with the `--plugin` argument on the command line. You can also pass plugin module names to a `nose2.main.PluggableTestProgram` using the `plugins` keyword argument.

### Outputting XML Test Reports

#### Note

New in version 0.2

Output test reports in junit-xml format.

This plugin implements `startTest()`, `testOutcome()` and `stopTestRun()` to compile and then output a test report in junit-xml format. By default, the report is written to a file called `nose2-junit.xml` in the current working directory.

You can configure the output filename by setting `path` in a `[junit-xml]` section in a config file. Unicode characters which are invalid in XML 1.0 are replaced with the U+FFFD replacement character. In the case that your software throws an error with an invalid byte string.

By default, the ranges of discouraged characters are replaced as well. This can be changed by setting the `keep_restricted` configuration variable to `True`.

By default, the arguments of parametrized and generated tests are not printed. For instance, the following code:

```
# a.py

from nose2 import tools

def test_gen():
    def check(a, b):
        assert a == b, '{}!={}'.format(a,b)

    yield check, 99, 99
    yield check, -1, -1
```

(continues on next page)

(continued from previous page)

```
@tools.params('foo', 'bar')
def test_params(arg):
    assert arg in ['foo', 'bar', 'baz']
```

Produces this XML by default:

```
<testcase classname="a" name="test_gen:1" time="0.000171"
  timestamp="2021-12-09T21:28:09.686611">
  <system-out />
</testcase>
<testcase classname="a" name="test_gen:2" time="0.000202"
  timestamp="2021-12-09T21:28:09.686813">
  <system-out />
</testcase>
<testcase classname="a" name="test_params:1" time="0.000159"
  timestamp="2021-12-09T21:28:09.686972">
  <system-out />
</testcase>
<testcase classname="a" name="test_params:2" time="0.000163"
  timestamp="2021-12-09T21:28:09.687135">
  <system-out />
</testcase>
```

But if `test_fullname` is `True`, then the following XML is produced:

```
<testcase classname="a" name="test_gen:1 (99, 99)" time="0.000213"
  timestamp="2021-12-09T21:28:09.686611">
  <system-out />
</testcase>
<testcase classname="a" name="test_gen:2 (-1, -1)" time="0.000194"
  timestamp="2021-12-09T21:28:09.687105">
  <system-out />
</testcase>
<testcase classname="a" name="test_params:1 ('foo')" time="0.000178"
  timestamp="2021-12-09T21:28:09.687283">
  <system-out />
</testcase>
<testcase classname="a" name="test_params:2 ('bar')" time="0.000187"
  timestamp="2021-12-09T21:28:09.687470">
  <system-out />
</testcase>
```

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.junitxml
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.junitxml`

## Configuration [junit-xml]

### always-on

**Default**  
False

**Type**  
boolean

### keep\_restricted

**Default**  
False

**Type**  
boolean

### path

**Default**  
nose2-junit.xml

**Type**  
str

### test\_fullname

**Default**  
False

**Type**  
boolean

### test\_properties

**Default**  
None

**Type**  
str

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[junit-xml]
always-on = False
keep_restricted = False
path = nose2-junit.xml
test_fullname = False
```

## Command-line options

**--junit-xml-path** FILE  
Output XML filename

**-X** DEFAULT, **--junit-xml** DEFAULT  
Generate junit-xml output report

**Plugin class reference: JUnitXmlReporter**

**class** nose2.plugins.junitxml.**JUnitXmlReporter**(\*args, \*\*kwargs)

Output junit-xml test report to file

**handleArgs**(event)

Read option from command line and override the value in config file when necessary

**startTest**(event)

Count test, record start time

**stopTestRun**(event)

Output xml tree to file

**testOutcome**(event)

Add test outcome to xml tree

**Sample output**

The XML test report for nose2's sample scenario with tests in a package looks like this:

```
<testsuite errors="1" failures="5" name="nose2-junit" skips="1" tests="25" time="0.004">
  <testcase classname="pkg1.test.test_things" name="test_gen:1" time="0.000141" />
  <testcase classname="pkg1.test.test_things" name="test_gen:2" time="0.000093" />
  <testcase classname="pkg1.test.test_things" name="test_gen:3" time="0.000086" />
  <testcase classname="pkg1.test.test_things" name="test_gen:4" time="0.000086" />
  <testcase classname="pkg1.test.test_things" name="test_gen:5" time="0.000087" />
  <testcase classname="pkg1.test.test_things" name="test_gen_nose_style:1" time="0.000085
  ↪ " />
  <testcase classname="pkg1.test.test_things" name="test_gen_nose_style:2" time="0.000090
  ↪ " />
  <testcase classname="pkg1.test.test_things" name="test_gen_nose_style:3" time="0.000085
  ↪ " />
  <testcase classname="pkg1.test.test_things" name="test_gen_nose_style:4" time="0.000087
  ↪ " />
  <testcase classname="pkg1.test.test_things" name="test_gen_nose_style:5" time="0.000086
  ↪ " />
  <testcase classname="pkg1.test.test_things" name="test_params_func:1" time="0.000093" /
  ↪ >
  <testcase classname="pkg1.test.test_things" name="test_params_func:2" time="0.000098">
    <failure message="test failure">Traceback (most recent call last):
      File "nose2/plugins/loader/parameters.py", line 162, in func
        return obj(*argSet)
      File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
  ↪ ", line 64, in test_params_func
        assert a == 1
  ↪ AssertionError
  ↪ </failure>
  ↪ </testcase>
  <testcase classname="pkg1.test.test_things" name="test_params_func_multi_arg:1" time=
  ↪ "0.000094" />
  <testcase classname="pkg1.test.test_things" name="test_params_func_multi_arg:2" time=
  ↪ "0.000089">
    <failure message="test failure">Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```

File "nose2/plugins/loader/parameters.py", line 162, in func
    return obj(*argSet)
File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
↪", line 69, in test_params_func_multi_arg
    assert a == b
AssertionError
</failure>
</testcase>
<testcase classname="pkg1.test.test_things" name="test_params_func_multi_arg:3" time=
↪"0.000096" />
<testcase classname="" name="test_fixt" time="0.000091" />
<testcase classname="" name="test_func" time="0.000084" />
<testcase classname="pkg1.test.test_things.SomeTests" name="test_failed" time="0.000113
↪">
    <failure message="test failure">Traceback (most recent call last):
    File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
↪", line 17, in test_failed
        assert False, "I failed"
AssertionError: I failed
</failure>
</testcase>
<testcase classname="pkg1.test.test_things.SomeTests" name="test_ok" time="0.000093" />
<testcase classname="pkg1.test.test_things.SomeTests" name="test_params_method:1" time=
↪"0.000099" />
<testcase classname="pkg1.test.test_things.SomeTests" name="test_params_method:2" time=
↪"0.000101">
    <failure message="test failure">Traceback (most recent call last):
    File "nose2/plugins/loader/parameters.py", line 144, in _method
        return method(self, *argSet)
    File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
↪", line 29, in test_params_method
        self.assertEqual(a, 1)
AssertionError: 2 != 1
</failure>
</testcase>
<testcase classname="pkg1.test.test_things.SomeTests" name="test_skippy" time="0.000104
↪">
    <skipped />
</testcase>
<testcase classname="pkg1.test.test_things.SomeTests" name="test_typeerr" time="0.
↪000096">
    <error message="test failure">Traceback (most recent call last):
    File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
↪", line 13, in test_typeerr
        raise TypeError("oops")
TypeError: oops
</error>
</testcase>
<testcase classname="pkg1.test.test_things.SomeTests" name="test_gen_method:1" time="0.
↪000094" />
<testcase classname="pkg1.test.test_things.SomeTests" name="test_gen_method:2" time="0.
↪000090">

```

(continues on next page)

(continued from previous page)

```

<failure message="test failure">Traceback (most recent call last):
  File "nose2/plugins/loader/generators.py", line 145, in method
    return func(*args)
  File "nose2/tests/functional/support/scenario/tests_in_package/pkg1/test/test_things.py
↪", line 24, in check
    assert x == 1
AssertionError
</failure>
</testcase>
</testsuite>

```

## Selecting tests with attributes

### Note

New in version 0.2

Filter tests by attribute, excluding any tests whose attributes do not match any of the specified attributes.

Attributes may be simple values or lists, and may be attributes of a test method (or function), a test case class, or the callable yielded by a generator test.

Given the following test module, the attrib plugin can be used to select tests in the following ways (and others!):

### Note

All examples assume the attrib plugin has been activated in a config file:

```

[unittest]
plugins = nose2.plugins.attrib

```

```

import unittest

class Test(unittest.TestCase):
    def test_fast(self):
        pass

    test_fast.fast = 1
    test_fast.layer = 2
    test_fast.flags = ["blue", "green"]

    def test_faster(self):
        pass

    test_faster.fast = 1
    test_faster.layer = 1
    test_faster.flags = ["red", "green"]

    def test_slow(self):

```

(continues on next page)



(continued from previous page)

```

    pass

    test_slow.fast = 0
    test_slow.slow = 1
    test_slow.layer = 2

    def test_slower(self):
        pass

    test_slower.slow = 1
    test_slower.layer = 3
    test_slower.flags = ["blue", "red"]

```

### Select tests having an attribute

Running nose2 like this:

```
nose2 -v -A fast
```

Runs these tests:

```

test_fast (attrib_example.Test) ... ok
test_faster (attrib_example.Test) ... ok

```

This selects all tests that define the attribute as any True value.

### Select tests that do not have an attribute

Running nose2 like this:

```
nose2 -v -A '!fast'
```

Runs these tests:

```

test_slow (attrib_example.Test) ... ok
test_slower (attrib_example.Test) ... ok

```

This selects all tests that define the attribute as a False value, *and those tests that do not have the attribute at all*.

### Select tests having an attribute with a particular value

Running nose2 like this:

```
nose2 -v -A layer=2
```

Runs these tests:

```

test_fast (attrib_example.Test) ... ok
test_slow (attrib_example.Test) ... ok

```

This selects all tests that define the attribute with a matching value. The attribute value of each test case is converted to a string before comparison with the specified value. Comparison is case-insensitive.

### Select tests having a value in a list attribute

Running nose2 like this:

```
nose2 -v -A flags=red
```

Runs these tests:

```
test_faster (attrib_example.Test) ... ok
test_slower (attrib_example.Test) ... ok
```

Since the `flags` attribute is a list, this test selects all tests with the value `red` in their `flags` attribute. Comparison done after string conversion and is case-insensitive.

### Select tests that do not have a value in a list attribute

Running nose2 like this:

```
nose2 -v -A '!flags=red'
```

Runs these tests:

```
test_fast (attrib_example.Test) ... ok
```

The result in this case can be somewhat counter-intuitive. What the `attrib` plugin selects when you negate an attribute that is in a list are only those tests that *have the list attribute but without the value* specified. Tests that do not have the attribute at all are *not* selected.

### Select tests using Python expressions

For more complex cases, you can use the `-E` command-line option to pass a Python expression that will be evaluated in the context of each test case. Only those test cases where the expression evaluates to `True` (and don't raise an exception) will be selected.

Running nose2 like this:

```
nose2 -v -E '"blue" in flags and layer > 2'
```

Runs only one test:

```
test_slower (attrib_example.Test) ... ok
```

### Command-line options

**-A** DEFAULT, **--attribute** DEFAULT

Select tests with matching attribute

**-E** DEFAULT, **--eval-attribute** DEFAULT

Select tests for whose attributes the given Python expression evaluates to `True`

### Plugin class reference: `AttributeSelector`

```
class nose2.plugins.attrib.AttributeSelector(*args, **kwargs)
```

Filter tests by attribute

**handleArgs(args)**

Register if any attribs defined

**moduleLoadedSuite(event)**

Filter event.suite by specified attributes

**Running Tests in Parallel with Multiple Processes****Note**

New in version 0.3

Use the `mp` plugin to enable distribution of tests across multiple processes. Doing this may speed up your test run if your tests are heavily IO or CPU bound. But it *imposes an overhead cost* that is not trivial, and it *complicates the use of test fixtures* and may *conflict with plugins that are not designed to work with it*.

**Usage**

To activate the plugin, include the plugin module in the plugins list in `[unittest]` section in a config file:

```
[unittest]
plugins = nose2.plugins.mp
```

Or pass the module with the `--plugin` command-line option:

```
nose2 --plugin=nose2.plugins.mp
```

Then configure the number of processes to run. You can do that either with the `-N` option:

```
nose2 -N 2
```

or by setting processes in the `[multiprocess]` section of a config file:

```
[multiprocess]
processes = 2
```

**Note**

If you make the plugin always active by setting `always-on` in the `[multiprocess]` section of a config file, but do not set `processes` or pass `-N`, the number of processes defaults to the number of CPUs available. Also note that a value of 0 will set the actual number of processes to the number of CPUs on the computer.

Should one wish to specify the use of internet sockets for interprocess communications, specify the `bind_address` setting in the `[multiprocess]` section of the config file, for example:

```
[multiprocess]
bind_address = 127.0.0.1:1024
```

This will bind to port 1024 of 127.0.0.1. Also:

```
[multiprocess]
bind_address = 127.1.2.3
```

will bind to any random open port on 127.1.2.3. Any internet address or host-name which python can recognize as such, bind, *and* connect is acceptable. While 0.0.0.0 can be use for listening, it is not necessarily an address to which the OS can connect. When the port address is 0 or omitted, a random open port is used. If the setting is omitted or blank, then sockets are not used unless nose is being executed on Windows. In which case, an address on the loop back interface and a random port are used. Whenever used, processes employ a random shared key for authentication.

## Guidelines for Test Authors

Not every test suite will work well, or work at all, when run in parallel. For some test suites, parallel execution makes no sense. For others, it will expose bugs and ordering dependencies in test cases and test modules.

## Overhead Cost

Starting subprocesses and dispatching tests takes time. A test run that includes a relatively small number of tests that are not I/O or CPU bound (or calling `time.sleep()`) is likely to be *slower* when run in parallel.

As of this writing, for instance, nose2's test suite takes about 10 times as long to run when using `multiprocessing`, due to the overhead cost.

## Shared Fixtures

The individual test processes do not share state or data after launch. This means *tests that share a fixture* – tests that are loaded from modules where `setUpModule` is defined, and tests in test classes that define `setUpClass` – *must all be dispatched to the same process at the same time*. So if you use these kinds of fixtures, your test runs may be less parallel than you expect.

## Tests Load Twice

Test cases may not be pickleable, so nose2 can't transmit them directly to its test runner processes. Tests are distributed by name. This means that *tests always load twice* – once in the main process, during initial collection, and then again in the test runner process, where they are loaded by name. This may be problematic for some test suites.

## Random Execution Order

Tests do not execute in the same order when run in parallel. Results will be returned in effectively random order, and tests in the same module (*as long as they do not share fixtures*) may execute in any order and in different processes. Some test suites have ordering dependencies, intentional or not, and those that do will fail randomly when run with this plugin.

## Guidelines for Plugin Authors

The `MultiProcess` plugin is designed to work with other plugins, but other plugins may have to return the favor, especially if they load tests or care about something that happens *during* test execution.

## New Methods

The `MultiProcess` plugin adds a few plugin hooks that other plugins can use to set themselves up for multiprocessing test runs. Plugins don't have to do anything special to register for these hooks; just implement the methods as normal.

**`registerInSubprocess(self, event)`**

### Parameters

**event** – `nose2.plugins.mp.RegisterInSubprocessEvent`

The `registerInSubprocess` hook is called after plugin registration to enable plugins that need to run in subprocesses to register that fact. The most common thing to do, for plugins that need to run in subprocesses, is:

```
def registerInSubprocess(self, event):
    event.pluginClasses.append(self.__class__)
```

It is not required that plugins append their own class. If for some reason there is a different plugin class, or set of classes, that should run in the test-running subprocesses, add that class or those classes instead.

**startSubprocess**(*self*, *event*)

**Parameters**

**event** – *nose2.plugins.mp.SubprocessEvent*

The startSubprocess hook fires in each test-running subprocess after it has loaded its plugins but before any tests are executed.

Plugins can customize test execution here in the same way as in *startTestRun()*, by setting *event.executeTests*, and prevent test execution by setting *event.handled* to True and returning False.

**stopSubprocess**(*self*, *event*)

**Parameters**

**event** – *nose2.plugins.mp.SubprocessEvent*

The stopSubprocess event fires just before each test running subprocess shuts down. Plugins can use this hook for any per-process finalization that they may need to do.

The same event instance is passed to *startSubprocess* and *stopSubprocess*, which enables plugins to use that event's metadata to communicate state or other information from the start to the stop hooks, if needed.

## New Events

The MultiProcess plugin's new hooks come with custom event classes.

**class** *nose2.plugins.mp.RegisterInSubprocessEvent*(*\*\*metadata*)

Event fired to notify plugins that multiprocessing testing will occur

**pluginClasses**

Add a plugin class to this list to cause the plugin to be instantiated in each test-running subprocess. The most common thing to do, for plugins that need to run in subprocesses, is:

```
def registerInSubprocess(self, event):
    event.pluginClasses.append(self.__class__)
```

**class** *nose2.plugins.mp.SubprocessEvent*(*loader*, *result*, *runner*, *plugins*, *connection*, *\*\*metadata*)

Event fired at start and end of subprocess execution.

**loader**

Test loader instance

**result**

Test result

**plugins**

List of plugins loaded in the subprocess.

**connection**

The multiprocessing.Connection instance that the subprocess uses for communication with the main process.

### executeTests

Callable that will be used to execute tests. Plugins may set this attribute to wrap or otherwise change test execution. The callable must match the signature:

```
def execute(suite, result):  
    ...
```

### Stern Warning

All event attributes, *including* `event.metadata`, *must be pickleable*. If your plugin sets any event attributes or puts anything into `event.metadata`, it is your responsibility to ensure that anything you can possibly put in is pickleable.

### Do I Really Care?

If you answer *yes* to any of the following questions, then your plugin will not work with multiprocessing testing without modification:

- Does your plugin load tests?
- Does your plugin capture something that happens during test execution?
- Does your plugin require user interaction during test execution?
- Does your plugin set `executeTests` in `startTestRun`?

Here's how to handle each of those cases.

### Loading Tests

- Implement `registerInSubprocess()` as suggested to enable your plugin in the test runner processes.

### Capturing Test Execution State

- Implement `registerInSubprocess()` as suggested to enable your plugin in the test runner processes.
- Be wary of setting `event.metadata` unconditionally. Your plugin will execute in the main process and in the test runner processes, and will see `setTestOutcome()` and `testOutcome()` events *in both processes*. If you unconditionally set a key in `event.metadata`, the plugin instance in the main process will overwrite anything set in that key by the instance in the subprocess.
- If you need to write something to a file, implement `stopSubprocess()` to write a file in each test runner process.

### Overriding Test Execution

- Implement `registerInSubprocess()` as suggested to enable your plugin in the test runner processes and make a note that your plugin is running under a multiprocessing session.
- When running multiprocessing, *do not* set `event.executeTests` in `startTestRun()` – instead, set it in `startSubprocess()` instead. This will allow the multiprocessing plugin to install its test executor in the main process, while your plugin takes over test execution in the test runner subprocesses.

### Interacting with Users

- You are probably safe because as a responsible plugin author you are already firing the interaction hooks (`beforeInteraction()`, `afterInteraction()`) around your interactive bits, and skipping them when the `beforeInteraction()` hook returns `False` and sets `event.handled`.

If you're not doing that, start!

## Possible Issues On Windows

On windows, there are a few known bugs with respect to multiprocessing.

Python on windows does not use `fork()`. It bootstraps from a separate interpreter invocation. In certain contexts, the “value” for a parameter will be taken as a “count” and subprocess use this to build the flag for the command-line. E.g., If this value is 2 billion (like a hash seed), subprocess.py may attempt to build a 2gig string, and possibly throw a `MemoryError` exception. The related bug is <http://bugs.python.org/issue20954>.

## Reference

### Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.mp
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.mp`

## Configuration [multiprocess]

### always-on

#### Default

False

#### Type

boolean

### bind\_address

#### Default

None

#### Type

str

### processes

#### Default

0

#### Type

integer

### test-run-timeout

#### Default

60.0

#### Type

float

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[multiprocess]
always-on = False
processes = 0
test-run-timeout = 60.0
```

## Command-line options

**-N** DEFAULT, **--processes** DEFAULT  
Number of processes used to run tests (0 = auto)

## Plugin class reference: MultiProcess

```
class nose2.plugins.mp.MultiProcess(*args, **kwargs)
```

### property procs

Get the appropriate number of procs for self.procs if self.\_procs is 0.

## Organizing Test Fixtures into Layers

### Note

New in version 0.4

Layers allow more flexible organization of test fixtures than test-, class- and module- level fixtures. Layers in nose2 are inspired by and aim to be compatible with the layers used by Zope's testrunner.

Using layers, you can do things like:

- Implement package-level fixtures by sharing a layer among all test cases in the package.
- Share fixtures across tests in different modules without having them run multiple times.
- Create a fixture tree deeper than three levels (test, class and module).
- Make fixtures available for other packages or projects to use.

A layer is a *new-style* class that implements at least a `setUp` classmethod:

```
class Layer(object):
    @classmethod
    def setUp(cls):
        # ...
```

It may also implement `tearDown`, `testSetUp` and `testTearDown`, all as classmethods.

To assign a layer to a test case, set the test case's `layer` property:

```
class Test(unittest.TestCase):
    layer = Layer
```

Note that the layer *class* is assigned, not an instance of the layer. Typically layer classes are not instantiated.



## Sub-layers

Layers may subclass other layers:

```
class SubLayer(Layer):
    @classmethod
    def setUp(cls):
        # ...
```

In this case, all tests that belong to the sub-layer also belong to the base layer. For example for this test case:

```
class SubTest(unittest.TestCase):
    layer = SubLayer
```

The `setUp` methods from *both* `SubLayer` and `Layer` will run before any tests are run. The superclass's setup will always run before the subclass's setup. For `tearDown`, the reverse: the subclass's `tearDown` runs before the superclass's.

### Warning

One important thing to note: layers that subclass other layers *must not* call their superclass's `setUp`, `tearDown`, etc. The test runner will take care of organizing tests so that the superclass's methods are called in the right order:

```
Layer.setUp ->
SubLayer.setUp ->
Layer.testSetUp ->
SubLayer.testSetUp ->
TestCase.setUp
TestCase.run
TestCase.tearDown
SubLayer.testTearDown <-
Layer.testTearDown <-
SubLayer.tearDown <-
Layer.tearDown <-
```

If a sublayer calls its superclass's methods directly, *those methods will be called twice*.

## Layer method reference

### class Layer

Not an actual class, but reference documentation for the methods layers can implement. There is no layer base class. Layers must be subclasses of `object` or other layers.

#### classmethod setUp(cls)

The layer's `setUp` method is called before any tests belonging to that layer are executed. If no tests belong to the layer (or one of its sub-layers) then the `setUp` method will not be called.

#### classmethod tearDown(cls)

The layer's `tearDown` method is called after any tests belonging to the layer are executed, if the layer's `setUp` method was called and did not raise an exception. It will not be called if the layer has no `setUp` method, or if that method did not run or did raise an exception.

#### classmethod testSetUp(cls[, test])

The layer's `testSetUp` method is called before each test belonging to the layer (and its sub-layers). If the method is defined to accept an argument, the test case instance is passed to the method. The method may also be defined to take no arguments.

```
classmethod testTearDown(cls[, test])
```

The layer's `testTearDown` method is called after each test belonging to the layer (and its sub-layers), if the layer also defines a `setUpTest` method and that method ran successfully (did not raise an exception) for this test case.

## Layers DSL

nose2 includes a DSL for setting up layer-using tests called “such”. Read all about it here: *[Such: a Functional-Test Friendly DSL](#)*.

## Pretty reports

The layers plugin module includes a second plugin that alters test report output to make the layer groupings more clear. When activated with the `--layer-reporter` command-line option (or via a config file), test output that normally looks like this:

```
test (test_layers.NoLayer) ... ok
test (test_layers.Outer) ... ok
test (test_layers.InnerD) ... ok
test (test_layers.InnerA) ... ok
test (test_layers.InnerA_1) ... ok
test (test_layers.InnerB_1) ... ok
test (test_layers.InnerC) ... ok
test2 (test_layers.InnerC) ... ok
```

-----  
Ran 8 tests in 0.001s

OK

Will instead look like this:

```
test (test_layers.NoLayer) ... ok
Base
  test (test_layers.Outer) ... ok
  LayerD
    test (test_layers.InnerD) ... ok
  LayerA
    test (test_layers.InnerA) ... ok
  LayerB
    LayerC
      test (test_layers.InnerC) ... ok
      test2 (test_layers.InnerC) ... ok
    LayerB_1
      test (test_layers.InnerB_1) ... ok
    LayerA_1
      test (test_layers.InnerA_1) ... ok
```

-----  
Ran 8 tests in 0.002s

OK

The layer reporter plugin can also optionally colorize the keywords (by default, ‘A’, ‘having’, and ‘should’) in output

from tests defined with the *such DSL*.

If you would like to change how the layer is displayed, set the `description` attribute.

```
class LayerD(Layer):
    description = '*** This is a very important custom layer description ***'
```

Now the output will be the following:

```
test (test_layers.NoLayer) ... ok
Base
  test (test_layers.Outer) ... ok
  *** This is a very important custom layer description ***
  test (test_layers.InnerD) ... ok
LayerA
  test (test_layers.InnerA) ... ok
LayerB
  LayerC
    test (test_layers.InnerC) ... ok
    test2 (test_layers.InnerC) ... ok
  LayerB_1
    test (test_layers.InnerB_1) ... ok
  LayerA_1
    test (test_layers.InnerA_1) ... ok
```

```
-----
Ran 8 tests in 0.002s
```

```
OK
```

## Warnings and Caveats

### Test case order and module isolation

Test cases that use layers will not execute in the same order as test cases that do not. In order to execute the layers efficiently, the test runner must reorganize *all* tests in the loaded test suite to group those having like layers together (and sub-layers under their parents). If you share layers across modules this may result in tests from one module executing interleaved with tests from a different module.

### Mixing layers with `setUpClass` and module fixtures

#### Don't cross the streams.

The implementation of class- and module-level fixtures in `unittest2` depends on introspecting the class hierarchy inside of the `unittest.TestSuite`. Since the suites that the layers plugin uses to organize tests derive from `unittest.BaseTestSuite` (instead of `unittest.TestSuite`), class- and module- level fixtures in `TestCase` classes that use layers will be ignored.

### Mixing layers and multiprocessing testing

In the initial release, *test suites using layers are incompatible with the multiprocessing plugin*. This should be fixed in a future release.

## Plugin reference

### Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.layers
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.layers`

### Configuration [layer-reporter]

#### **always-on**

**Default**  
False

**Type**  
boolean

#### **colors**

**Default**  
False

**Type**  
boolean

#### **highlight-words**

**Default**  
['A', 'having', 'should']

**Type**  
list

#### **indent**

**Default**  
**Type**  
str

### Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[layer-reporter]
always-on = False
colors = False
highlight-words = A
                  having
                  should
indent =
```

## Command-line options

**--layer-reporter** DEFAULT

Add layer information to test reports

## Plugin class reference: LayerReporter

```
class nose2.plugins.layers.LayerReporter(*args, **kwargs)
```

## Plugin class reference: Layers

```
class nose2.plugins.layers.Layers(*args, **kwargs)
```

## Loader: Doctests

Load tests from doctests.

This plugin implements [handleFile\(\)](#) to load doctests from text files and python modules.

To disable loading doctests from text files, configure an empty extensions list:

```
[doctest]
extensions =
```

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.doctests
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.doctests`

## Configuration [doctest]

### always-on

#### Default

False

#### Type

boolean

### extensions

#### Default

['.txt', '.rst']

#### Type

list

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[doctest]
always-on = False
extensions = .txt
            .rst
```

## Command-line options

**--with-doctest** DEFAULT

Load doctests from text files and modules

## Plugin class reference: DocTestLoader

**class** nose2.plugins.doctests.DocTestLoader(\*args, \*\*kwargs)

**handleFile**(event)

Load doctests from text files and modules

## Mapping exceptions to test outcomes

Map exceptions to test outcomes.

This plugin implements `setTestOutcome()` to enable simple mapping of exception classes to existing test outcomes.

By setting a list of exception classes in a nose2 config file, you can configure exceptions that would otherwise be treated as test errors, to be treated as failures or skips instead:

```
[outcomes]
always-on = True
treat-as-fail = NotImplementedError
treat-as-skip = TodoError
               IOError
```

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.outcomes
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.outcomes`

## Configuration [outcomes]

**always-on**

**Default**

False

**Type**  
boolean

**treat-as-fail**

**Default**  
[]

**Type**  
list

**treat-as-skip**

**Default**  
[]

**Type**  
list

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[outcomes]
always-on = False
treat-as-fail =
treat-as-skip =
```

## Command-line options

**--set-outcomes** DEFAULT

Treat some configured exceptions as failure or skips

## Plugin class reference: Outcomes

**class** nose2.plugins.outcomes.Outcomes(\*args, \*\*kwargs)

Map exceptions to other test outcomes

**setTestOutcome**(event)

Update outcome, exc\_info and reason based on configured mappings

## Collecting tests without running them

This plugin implements `startTestRun()`, setting a test executor (`event.executeTests`) that just collects tests without executing them. To do so it calls `result.startTest`, `result.addSuccess` and `result.stopTest` for each test, without calling the test itself.

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.collect
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.collect`

## Configuration [collect-only]

### always-on

**Default**

False

**Type**

boolean

### Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[collect-only]
always-on = False
```

## Command-line options

**--collect-only** DEFAULT

Collect but do not run tests. With '-v', this will output test names

### Plugin class reference: `CollectOnly`

**class** `nose2.plugins.collect.CollectOnly(*args, **kwargs)`

Collect but don't run tests

**collectTests**(*suite, result*)

Collect tests, but don't run them

**startTestRun**(*event*)

Replace `event.executeTests`

## Using Test IDs

Allow easy test selection with test ids.

Assigns (and, in verbose mode, prints) a sequential test id for each test executed. Ids can be fed back in as test names, and this plugin will translate them back to full test names. Saves typing!

This plugin implements `reportStartTest()`, `loadTestsFromName()`, `loadTestsFromNames()` and `stopTest()`.

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.testid
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.testid`



## Configuration [testid]

### always-on

**Default**  
False

**Type**  
boolean

### id-file

**Default**  
.noseids

**Type**  
str

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[testid]
always-on = False
id-file = .noseids
```

## Command-line options

**-I** DEFAULT, **--with-id** DEFAULT  
Add test ids to output

## Plugin class reference: TestId

**class** nose2.plugins.testid.TestId(\*args, \*\*kwargs)

Allow easy test select with ids

**loadIds()**

Load previously pickled 'ids' and 'tests' attributes.

**loadTestsFromName(event)**

Load tests from a name that is an id

If the name is a number, it might be an ID assigned by us. If we can find a test to which we have assigned that ID, event.name is changed to the test's real ID. In this way, tests can be referred to via sequential numbers.

**loadTestsFromNames(event)**

Translate test ids into test names

**nextId()**

Increment ID and return it.

**reportStartTest(event)**

Record and possibly output test id

**stopTestRun(event)**

Write testids file

## Profiling

Profile test execution using cProfile.

This plugin implements `startTestRun()` and replaces `event.executeTests` with `cProfile.Profile.runcall()`. It implements `beforeSummaryReport()` to output profiling information before the final test summary time. Config file options `filename`, `sort` and `restrict` can be used to change where profiling information is saved and how it is presented.

Load this plugin by running nose2 with the `-plugin=nose2.plugins.prof` option and activate it with the `-profile` option, or put the corresponding entries (`plugin` and `always_on`) in the respective sections of the configuration file.

### Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.prof
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.prof`

### Configuration [profiler]

#### `always-on`

**Default**

False

**Type**

boolean

#### `filename`

**Default****Type**

str

#### `restrict`

**Default**

[]

**Type**

list

#### `sort`

**Default**

cumulative

**Type**

str

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[profiler]
always-on = False
filename =
restrict =
sort = cumulative
```

## Command-line options

**-P** DEFAULT, **--profile** DEFAULT

Run tests under profiler

## Plugin class reference: Profiler

**class** nose2.plugins.prof.**Profiler**(\*args, \*\*kwargs)

Profile the test run

**beforeSummaryReport**(event)

Output profiling results

**startTestRun**(event)

Set up the profiler

## Tracing hook execution

This plugin is primarily useful for plugin authors who want to debug their plugins.

It prints each hook that is called to stderr, along with details of the event that was passed to the hook.

To do that, this plugin overrides `nose2.events.Plugin.register()` and, after registration, replaces all existing `nose2.events.Hook` instances in `session.hooks` with instances of a `Hook` subclass that prints information about each call.

## Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.printhooks
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.printhooks`

## Configuration [print-hooks]

### always-on

**Default**

False

**Type**

boolean

## Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[print-hooks]
always-on = False
```

## Command-line options

**-P** DEFAULT, **--print-hooks** DEFAULT  
 Print names of hooks in order of execution

## Plugin class reference: `PrintHooks`

**class** nose2.plugins.printhooks.**PrintHooks**(\*args, \*\*kwargs)  
 Print hooks as they are called

**register()**  
 Override to inject noisy hook instances.  
 Replaces *Hook* instances in `self.session.hooks.hooks` with noisier objects.

## Sample output

`PrintHooks` output for a test run that discovers one standard `TestCase` test in a python module.

Hooks that appear indented are called from within other hooks.

```
handleArgs: CommandLineArgsEvent(handled=False, args=Namespace(collect_only=None,
↳ config=['unittest.cfg', 'nose2.cfg'], debugger=None, fail_fast=None, load_plugins=True,
↳ log_level=30, print_hooks=None, profile=None, start_dir='.', testNames=[], top_level_
↳ directory=None, user_config=True, verbose=0, with_id=None))

createTests: CreateTestsEvent(loader=<PluggableTestLoader>, testNames=[], module=<module
↳ '__main__' from 'bin/nose2'>)

loadTestsFromNames: LoadFromNames(names=[], module=None)

    handleFile: HandleFileEvent(handled=False, loader=<PluggableTestLoader>, name='tests.py'
↳ ', path='nose2/tests/functional/support/scenario/one_test/tests.py', pattern='test*.py'
↳ ', topLevelDirectory='nose2/tests/functional/support/scenario/one_test')

    matchPath: MatchPathEvent(handled=False, name='tests.py', path='nose2/tests/functional/
↳ support/scenario/one_test/tests.py', pattern='test*.py')

    loadTestsFromModule: LoadFromModuleEvent(handled=False, loader=<PluggableTestLoader>,
↳ module=<module 'tests' from 'nose2/tests/functional/support/scenario/one_test/tests.py'
↳ '>, extraTests=[])

    loadTestsFromTestCase: LoadFromTestCaseEvent(handled=False, loader=
↳ <PluggableTestLoader>, testCase=<class 'tests.Test'>, extraTests=[])

    getTestCaseNames: GetTestCaseNamesEvent(handled=False, loader=<PluggableTestLoader>,
↳ testCase=<class 'tests.Test'>, testMethodPrefix=None, extraNames=[], excludedNames=[],
```

(continues on next page)

(continued from previous page)

```

→isTestMethod=<function isTestMethod at 0x1fccc80>)

    handleFile: HandleFileEvent(handled=False, loader=<PluggableTestLoader>, name='tests.
→pyc', path='nose2/tests/functional/support/scenario/one_test/tests.pyc', pattern=
→'test*.py', topLevelDirectory='nose2/tests/functional/support/scenario/one_test')

runnerCreated: RunnerCreatedEvent(handled=False, runner=<PluggableTestRunner>)

resultCreated: ResultCreatedEvent(handled=False, result=<PluggableTestResult>)

startTestRun: StartTestRunEvent(handled=False, runner=<PluggableTestRunner>, suite=
→<unittest2.suite.TestSuite tests=[<unittest2.suite.TestSuite tests=[<unittest2.suite.
→TestSuite tests=[<tests.Test testMethod=test>]>]>]>, result=<PluggableTestResult>,
→startTime=1327346684.77457, executeTests=<function <lambda> at 0x1fccf50>)

startTest: StartTestEvent(handled=False, test=<tests.Test testMethod=test>, result=
→<PluggableTestResult>, startTime=1327346684.774765)

    reportStartTest: ReportTestEvent(handled=False, testEvent=<nose2.events.StartTestEvent
→object at 0x1fcd650>, stream=<nose2.util._WritelnDecorator object at 0x1f97a10>)

setTestOutcome: TestOutcomeEvent(handled=False, test=<tests.Test testMethod=test>,
→result=<PluggableTestResult>, outcome='passed', exc_info=None, reason=None,
→expected=True, shortLabel=None, longLabel=None)

testOutcome: TestOutcomeEvent(handled=False, test=<tests.Test testMethod=test>, result=
→<PluggableTestResult>, outcome='passed', exc_info=None, reason=None, expected=True,
→shortLabel=None, longLabel=None)

    reportSuccess: ReportTestEvent(handled=False, testEvent=<nose2.events.TestOutcomeEvent
→object at 0x1fcd650>, stream=<nose2.util._WritelnDecorator object at 0x1f97a10>)
.
stopTest: StopTestEvent(handled=False, test=<tests.Test testMethod=test>, result=
→<PluggableTestResult>, stopTime=1327346684.775064)

stopTestRun: StopTestRunEvent(handled=False, runner=<PluggableTestRunner>, result=
→<PluggableTestResult>, stopTime=1327346684.77513, timeTaken=0.00056004524230957031)

afterTestRun: StopTestRunEvent(handled=False, runner=<PluggableTestRunner>, result=
→<PluggableTestResult>, stopTime=1327346684.77513, timeTaken=0.00056004524230957031)

    beforeErrorList: ReportSummaryEvent(handled=False, stopTestEvent=<nose2.events.
→StopTestRunEvent object at 0x1eb0d90>, stream=<nose2.util._WritelnDecorator object at
→0x1f97a10>, reportCategories={'failures': [], 'skipped': [], 'errors': [],
→'unexpectedSuccesses': [], 'expectedFailures': []})
-----

    beforeSummaryReport: ReportSummaryEvent(handled=False, stopTestEvent=<nose2.events.
→StopTestRunEvent object at 0x1eb0d90>, stream=<nose2.util._WritelnDecorator object at
→0x1f97a10>, reportCategories={'failures': [], 'skipped': [], 'errors': [],
→'unexpectedSuccesses': [], 'expectedFailures': []})

```

(continues on next page)

(continued from previous page)

```
Ran 1 test in 0.001s
```

```
wasSuccessful: ResultSuccessEvent(handled=False, result=<PluggableTestResult>,
↳ success=False)
```

```
OK
```

```
afterSummaryReport: ReportSummaryEvent(handled=False, stopTestEvent=<nose2.events.
↳ StopTestRunEvent object at 0x1eb0d90>, stream=<nose2.util._WriteInDecorator object at
↳ 0x1f97a10>, reportCategories={'failures': [], 'skipped': [], 'errors': [],
↳ 'unexpectedSuccesses': [], 'expectedFailures': []})
```

## Loader: Egg Test discovery

### What is Egg Discovery

Sometimes Python Eggs are marked as zip-safe and they can be installed zipped, instead of unzipped in an .egg folder. See <http://peak.telecommunity.com/DevCenter/PythonEggs> for more details. The normal `nose2.plugins.loader.discovery` plugin ignores modules located inside zip files.

The Egg Discovery plugin allows nose2 to discover tests within these zipped egg files.

This plugin requires `pkg_resources` (from `setuptools`) to work correctly.

### Usage

To activate the plugin, include the plugin module in the plugins list in `[unittest]` section in a config file:

```
[unittest]
plugins = nose2.plugins.loader.eggdiscovery
```

Or pass the module with the `--plugin` command-line option:

```
nose2 --plugin=nose2.plugins.loader.eggdiscovery module_in_egg
```

## Reference

Egg-based discovery test loader.

This plugin implements nose2's automatic test module discovery inside Egg Files. It looks for test modules in packages whose names start with `test`, then fires the `loadTestsFromModule()` hook for each one to allow other plugins to load the actual tests.

It also fires `handleFile()` for every file that it sees, and `matchPath()` for every Python module, to allow other plugins to load tests from other kinds of files and to influence which modules are examined for tests.

### Enable this Plugin

This plugin is built-in, but not loaded by default.

Even if you specify `always-on = True` in the configuration, it will not run unless you also enable it. You can do so by putting the following in a `unittest.cfg` or `nose2.cfg` file

```
[unittest]
plugins = nose2.plugins.loader.eggdiscovery
```

The `plugins` parameter may contain a list of plugin names, including `nose2.plugins.loader.eggdiscovery`

### Configuration [discovery]

#### always-on

**Default**

True

**Type**

boolean

#### Sample configuration

The default configuration is equivalent to including the following in a `unittest.cfg` file.

```
[discovery]
always-on = True
```

#### Plugin class reference: `EggDiscoveryLoader`

**class** `nose2.plugins.loader.eggdiscovery.EggDiscoveryLoader(*args, **kwargs)`

Loader plugin that can discover tests inside Egg Files

**loadTestsFromName**(*event*)

Load tests from module named by `event.name`

**loadTestsFromNames**(*event*)

Discover tests if no test names specified

## 7.5.3 Third-party Plugins

If you are a plugin author, please add your plugin to the list on the [nose2 wiki](#). If you are looking for more plugins, check that list!

## 7.6 Tools and Helpers

### 7.6.1 Tools for Test Authors

#### Decorators

nose2 ships with various decorators that assist you to write your tests.

#### Setup & Teardown

`nose2.tools.decorators.with_setup(setup)`

A decorator that sets the `setup()` method to be executed before the test.

It currently works only for function test cases.

**Parameters**

**setup** (*function*) – The method to be executed before the test.

`nose2.tools.decorators.with_teardown(teardown)`

A decorator that sets the `teardown()` method to be after before the test.

It currently works only for function test cases.

**Parameters**

**`teardown`** (*function*) – The method to be executed after the test.

## Parameterized tests

`nose2.tools.params(*paramList)`

Make a test function or method parameterized by parameters.

```
import unittest

from nose2.tools import params

@params(1, 2, 3)
def test_nums(num):
    assert num < 4

class Test(unittest.TestCase):

    @params((1, 2), (2, 3), (4, 5))
    def test_less_than(self, a, b):
        assert a < b
```

Parameters in the list may be defined as simple values, or as tuples. To pass a tuple as a simple value, wrap it in another tuple.

See also: *Loader: Parameterized Tests*

## Such: a Functional-Test Friendly DSL

### Note

New in version 0.4

Such is a DSL for writing tests with expensive, nested fixtures – which typically means functional tests. It requires the layers plugin (see *Organizing Test Fixtures into Layers*).

### What does it look like?

Unlike some python testing DSLs, such is just plain old python.

```
import unittest

from nose2.tools import such

class SomeLayer:
    @classmethod
```

(continues on next page)



(continued from previous page)

```

def setUp(cls):
    it.somelayer = True

@classmethod
def tearDown(cls):
    del it.somelayer

#
# Such tests start with a declaration about the system under test
# and will typically bind the test declaration to a variable with
# a name that makes nice sentences, like 'this' or 'it'.
#
with such.A("system with complex setup") as it:
    #
    # Each layer of tests can define setup and teardown methods.
    # setup and teardown methods defined here run around the entire
    # group of tests, not each individual test.
    #
    @it.has_setup
    def setup():
        it.things = [1]

    @it.has_teardown
    def teardown():
        it.things = []

    #
    # The 'should' decorator is used to mark tests.
    #
    @it.should("do something")
    def test():
        assert it.things
        #
        # Tests can use all of the normal unittest TestCase assert
        # methods by calling them on the test declaration.
        #
        it.assertEqual(len(it.things), 1)

    #
    # The 'having' context manager is used to introduce a new layer,
    # one that depends on the layer(s) above it. Tests in this
    # new layer inherit all of the fixtures of the layer above.
    #
    with it.having("an expensive fixture"):

        @it.has_setup
        def setup(): # noqa: F811
            it.things.append(2)

        #
        # Tests that take an argument will be passed the

```

(continues on next page)

(continued from previous page)

```

# unittest.TestCase instance that is generated to wrap
# them. Tests can call any and all TestCase methods on this
# instance.
#
@it.should("do more things")
def test(case): # noqa: F811
    case.assertEqual(it.things[-1], 2)

#
# Layers can be nested to any depth.
#
with it.having("another precondition"):

    @it.has_setup
    def setup(): # noqa: F811
        it.things.append(3)

    @it.has_teardown
    def teardown(): # noqa: F811
        it.things.pop()

    @it.should("do that not this") # type: ignore[no-redef]
    def test(case): # noqa: F811
        it.things.append(4)
        #
        # Tests can add their own cleanup functions.
        #
        case.addCleanup(it.things.pop)
        case.assertEqual(it.things[-1], 4, it.things)

    @it.should("do this not that") # type: ignore[no-redef]
    def test(case): # noqa: F811
        case.assertEqual(it.things[-1], 3, it.things[:])

#
# A layer may have any number of sub-layers.
#
with it.having("a different precondition"):
    #
    # A layer defined with ``having`` can make use of
    # layers defined elsewhere. An external layer
    # pulled in with ``it.uses`` becomes a parent
    # of the current layer (though it doesn't actually
    # get injected into the layer's MRO).
    #
    it.uses(SomeLayer)

    @it.has_setup
    def setup(): # noqa: F811
        it.things.append(99)

    @it.has_teardown

```

(continues on next page)

(continued from previous page)

```

def teardown(): # noqa: F811
    it.things.pop()

#
# Layers can define setup and teardown methods that wrap
# each test case, as well, corresponding to TestCase.setUp
# and TestCase.tearDown.
#
@it.has_test_setup
def test_setup(case):
    it.is_funny = True
    case.is_funny = True

@it.has_test_teardown
def test_teardown(case):
    delattr(it, "is_funny")
    delattr(case, "is_funny")

@it.should("do something else") # type: ignore[no-redef]
def test(case): # noqa: F811
    assert it.things[-1] == 99
    assert it.is_funny
    assert case.is_funny

@it.should("have another test") # type: ignore[no-redef]
def test(case): # noqa: F811
    assert it.is_funny
    assert case.is_funny

@it.should("have access to an external fixture") # type: ignore[no-redef]
def test(case): # noqa: F811
    assert it.somelayer

with it.having("a case inside the external fixture"):

    @it.should("still have access to that fixture") # type: ignore[no-
↪redef] # noqa: E501
    def test(case): # noqa: F811
        assert it.somelayer

#
# To convert the layer definitions into test cases, you have to call
# `createTests` and pass in the module globals, so that the test cases
# and layer objects can be inserted into the module.
#
it.createTests(globals())

#
# Such tests and normal tests can coexist in the same modules.
#

```

(continues on next page)

(continued from previous page)

```
class NormalTest(unittest.TestCase):
    def test(self):
        pass
```

The tests it defines are unittest tests, and can be used with nose2 with just the layers plugin. You also have the option of activating a reporting plugin (*nose2.plugins.layers.LayerReporter*) to provide a more discursive brand of output:

```
test (test_such.NormalTest) ... ok
A system with complex setup
  should do something ... ok
  having an expensive fixture
    should do more things ... ok
    having another precondition
      should do that not this ... ok
      should do this not that ... ok
    having a different precondition
      should do something else ... ok
      should have another test ... ok
```

```
-----
Ran 7 tests in 0.002s
```

```
OK
```

## How does it work?

Such uses the things in python that are most like anonymous code blocks to allow you to construct tests with meaningful names and deeply-nested fixtures. Compared to DSLs in languages that do allow blocks, it is a little bit more verbose – the block-like decorators that mark fixture methods and test cases need to decorate *something*, so each fixture and test case has to have a function definition. You can use the same function name over and over here, or give each function a meaningful name.

The set of tests begins with a description of the system under test as a whole, marked with the A context manager:

```
from nose2.tools import such

with such.A('system described here') as it:
    # ...
```

Groups of tests are marked by the having context manager:

```
with it.having('a description of a group'):
    # ...
```

Within a test group (including the top-level group), fixtures are marked with decorators:

```
@it.has_setup
def setup():
    # ...

@it.has_test_setup
```

(continues on next page)

(continued from previous page)

```
def setup_each_test_case():
    # ...
```

And tests are likewise marked with the `should` decorator:

```
@it.should('exhibit the behavior described here')
def test(case):
    # ...
```

Test cases may optionally take one argument. If they do, they will be passed the `unittest.TestCase` instance generated for the test. They can use this `TestCase` instance to execute assert methods, among other things. Test functions can also call assert methods on the top-level scenario instance, if they don't take the `case` argument:

```
@it.should("be able to use the scenario's assert methods")
def test():
    it.assertEqual(something, 'a value')

@it.should("optionally take an argument")
def test(case):
    case.assertEqual(case.attribute, 'some value')
```

Finally, to actually generate tests, you **must** call `createTests` on the top-level scenario instance:

```
it.createTests(globals())
```

This call generates the `unittest.TestCase` instances for all of the tests, and the layer classes that hold the fixtures defined in the test groups. See *Organizing Test Fixtures into Layers* for more about test layers.

## Running tests

Since order is often significant in functional tests, **such DSL tests always execute in the order in which they are defined in the module**. Parent groups run before child groups, and sibling groups and sibling tests within a group execute in the order in which they are defined.

Otherwise, tests written in the such DSL are collected and run just like any other tests, with one exception: their names. The name of a such test case is the name of its immediately surrounding group, plus the description of the test, prepended with `test ####:`, where `####` is the test's (0-indexed) position within its group.

To run a case individually, you must pass in this full name – usually you'll have to quote it. For example, to run the case `should do more things` defined above (assuming the layers plugin is activated by a config file, and the test module is in the normal path of test collection), you would run nose2 like this:

```
nose2 "test_such.having an expensive fixture.test 0000: should do more things"
```

That is, for the generated test case, the **group description** is the **class name**, and the **test case description** is the **test case name**. As you can see if you run an individual test with the layer reporter active, all of the group fixtures execute in proper order when a test is run individually:

```
$ nose2 "test_such.having an expensive fixture.test 0000: should do more things"
A system with complex setup
  having an expensive fixture
    should do more things ... ok
```

(continues on next page)

(continued from previous page)

```
Ran 1 test in 0.000s
```

```
OK
```

## Reference

`nose2.tools.such.A(description)`

Test scenario context manager.

Returns a `nose2.tools.such.Scenario` instance, which by convention is bound to `it`:

```
with such.A('test scenario') as it:
    # tests and fixtures
```

**class** `nose2.tools.such.Scenario(description)`

A test scenario.

A test scenario defines a set of fixtures and tests that depend on those fixtures.

**createTests(mod)**

Generate test cases for this scenario.

### Warning

You must call this, passing in `globals()`, to generate tests from the scenario. If you don't, **no tests will be created**.

```
it.createTests(globals())
```

**has\_setup(func)**

Add a `setup()` method to this group.

The `setup()` method will run once, before any of the tests in the containing group.

A group may define any number of `setup()` functions. They will execute in the order in which they are defined.

```
@it.has_setup
def setup():
    # ...
```

**has\_teardown(func)**

Add a `teardown()` method to this group.

The `teardown()` method will run once, after all of the tests in the containing group.

A group may define any number of `teardown()` functions. They will execute in the order in which they are defined.

```
@it.has_teardown
def teardown():
    # ...
```

**has\_test\_setup(func)**

Add a test case `setup()` method to this group.

The `setup()` method will run before each of the tests in the containing group.

A group may define any number of test case `setup()` functions. They will execute in the order in which they are defined.

Test `setup()` functions may optionally take one argument. If they do, they will be passed the `unittest.TestCase` instance generated for the test.

```
@it.has_test_setup
def setup(case):
    # ...
```

**has\_test\_teardown(func)**

Add a test case `teardown()` method to this group.

The `teardown()` method will run before each of the tests in the containing group.

A group may define any number of test case `teardown()` functions. They will execute in the order in which they are defined.

Test `teardown()` functions may optionally take one argument. If they do, they will be passed the `unittest.TestCase` instance generated for the test.

```
@it.has_test_teardown
def teardown(case):
    # ...
```

**having(description)**

Define a new group under the current group.

Fixtures and tests defined within the block will belong to the new group.

```
with it.having('a description of this group'):
    # ...
```

**should(desc)**

Define a test case.

Each function marked with this decorator becomes a test case in the current group.

The decorator takes one optional argument, the description of the test case: what it **should** do. If this argument is not provided, the docstring of the decorated function will be used as the test case description.

Test functions may optionally take one argument. If they do, they will be passed the `unittest.TestCase` instance generated for the test. They can use this `TestCase` instance to execute assert methods, among other things.

```
@it.should('do this')
def dothis(case):
    # ....

@it.should
def dothat():
    "do that also"
    # ....
```

## 7.7 Changelog

nose2 uses semantic versioning (currently in 0.x) and the popular “keep a changelog” format (v1.0.0).

nose2 tries not to break backwards compatibility in any release. Until v1.0, versions are numbered `0.MAJOR.MINOR`. Major releases introduce new functionality or contain necessary breaking changes. Minor releases are primarily used for bugfix or small features which are unlikely to break users’ testsuites.

### 7.7.1 Unreleased

#### 7.7.2 0.15.1 (2024-05-31)

##### Fixed

- Fix a bug with config loading which caused custom ini configs not to load if they were not named with a `.cfg` extension. Thanks [:user:grhwalls](#) for the bug report!

#### 7.7.3 0.15.0 (2024-05-30)

##### Added

- Official support for python3.13 betas. nose2 now tests itself against Python 3.13.
- nose2 now supports loading configuration data from the `tool.nose2` table in `pyproject.toml`. Thanks to [:user:qequ](#) for the PR! ([:pr:596](#), [:pr:606](#))

On python 3.11+, `tomllib` is used to parse TOML data. On python 3.10 and lower, `tomli` must be installed to enable TOML support. Simply `pip install tomli` as necessary.

#### 7.7.4 0.14.2 (2024-05-07)

##### Added

- For the coverage plugin, add a config option, `coverage-combine`, which defaults to `False`. When set, this config invokes a `coverage combine` step before reporting results, regardless of whether or not multiprocessing was used to run tests. This allows reporting of coverage results via the plugin on testsuites which invoke subprocesses. Thanks to [:user:JCHacking](#) for the PR! ([:pr:601](#))

#### 7.7.5 0.14.1 (2024-01-28)

##### Fixed

- Fix the reporting of skipped tests in verbose mode on newer pythons (3.12.1+), in which a skipped test is no longer treated as “started”.

nose2 will not introduce a `StartTestEvent` in such cases – the fix is narrowly and adjustment to the test reporter.

#### 7.7.6 0.14.0 (2023-10-04)

##### Added

- Add official support for python3.12



**Removed**

- Remove support for python3.6 and python3.7

**7.7.7 0.13.0 (2023-04-29)****Changed**

- nose2 package metadata is converted to pyproject.toml format, using setuptools. Building nose2 packages from source now requires setuptools>=61.0.0 or a PEP 517 compatible build frontend (e.g. build).

**Fixed**

- Fix support for python3.12 to avoid warnings about addDuration. Thanks to :user:`cclauss` for the fix!
- nose2 license metadata has been corrected in format and content to be distributed in the sdist and wheel distributions correctly. Thanks :user:`musicinmybrain` for helping research this issue!

**Removed**

- Remove support for python2 and older python3 versions

**7.7.8 0.12.0 (2022-07-16)****Note**

The 0.12.x series will be the final releases of nose2 which support Python 2.

**Changed**

- Passing `--junit-xml-path` now implies `--junit-xml` when using the junitxml plugin. This means that the `--junit-xml` flag can be omitted when `--junit-xml-path` is specified. (:issue:`521`)
- Remove the dependency on coverage. Use of the coverage plugin now requires that you either install coverage independently, or use the extra, `nose2[coverage_plugin]`. As a result, nose2 no longer has any strict dependencies
- Remove the dependency on six, instead using a vendored copy. This ensures that the dependency for nose2 doesn't conflict with application dependencies

**Removed**

- nose2 no longer provides an entry-point named based on the current python version, e.g. `nose2-3.8` on python3.8. Only the `nose2` command is provided.
- Remove support for `setup.py test` on nose2 itself. This usage is deprecated by setuptools. Developers contributing to nose2 are encouraged to use `tox` to run nose2's testsuite, per the contributing guide.

**7.7.9 0.11.0 (2022-02-12)**

This is the first version of *nose2* using *sphinx-issues* to credit contributors in the changelog.

**Added**

- Test classes now have their short description (first line of docstring) printed in verbose output
- The junitxml plugin now sets `timestamp` on each `testcase` node as an ISO-8601 timestamp. Thanks to :user:`deeplow` for the contribution!

## Changed

- Drop support for Python 3.5
- Python 3.10 is now officially supported. Python 3.11-dev will be supported on a best-effort basis. Thanks to [:user:`hugovk`](#) and [:user:`tirkarthy`](#) for their contributions!
- nose2 source code is now autoformatted with `black` and `isort`
- nose2 has switched its main development branch from `master` to `main`
- Releases are now published using `build`

## Fixed

- Add support for test classes when running with the multiprocessing plugin. Thanks to [:user:`Itfish`](#) for the initial contribution and [:user:`stefanholek`](#) for the refinement to this change!
- Various documentation fixes

## 7.7.10 0.10.0 (2021-01-27)

### Added

- Support for subtests!

Notes for plugin authors about subtest support:

- Subtest failures will produce a `TestOutcomeEvent` with `outcome = "subtest"`
- Subtest events can be failures, but they do not indicate success – the containing test will send a success event if no subtests fail

### Changed

- Drop support for Python 3.4
- Python 3.8 and 3.9 are now officially supported
- Improve helptext for the multiprocess plugin's `-N` option
- When run with reduced verbosity (e.g. with `-q`), nose2 will no longer print an empty line before test reports

### Fixed

- The plugin registry will no longer contain duplicate plugins and or base `event.Plugin` instances
- Fix function test case implementation of `id`, `__str__`, and `__repr__`. This removes the injected `transplant_class.<locals>` from reporting output
- Doctest loading will now skip `setup.py` files in the project root
- Class methods decorated (e.g. with `mock.patch`) are no longer incorrectly picked up by the function loader

## 7.7.11 0.9.2 (2020-02-02)

### Added

- Add `--junit-xml-path` to the junit plugin argument list

**Fixed**

- It is now possible to use the multiprocessing and coverage plugins together, as long as all of the coverage config is put into the config file
- Minor changes to be compatible with newer pythons (3.8, 3.9)

**7.7.12 0.9.1 (2019-04-02)****Changed**

- the prof plugin now uses `cProfile` instead of `hotshot` for profiling, and therefore now supports python versions which do not include `hotshot`
- skipped tests now include the user's reason in junit XML's message field

**Fixed**

- the prettyassert plugin mishandled multi-line function definitions
- Using a plugin's CLI flag when the plugin is already enabled via config no longer errors – it is a no-op instead

**7.7.13 0.9.0 (2019-03-17)****Added**

- `nose2.plugins.prettyassert`, enabled with `--pretty-assert`, which pretty-prints `AssertionErrors` generated by `assert` statements

**Changed**

- Update trove classifier to “beta” from “alpha” status
- Cleanup code for EOLed python versions

**Removed**

- Dropped support for `distutils`. Installation now requires `setuptools`

**Fixed**

- Result reporter respects failure status set by other plugins
- JUnit XML plugin now includes the skip reason in its output

**7.7.14 0.8.0 (2018-07-31)****Added**

- Add code to enable plugins to documentation

**Removed**

- Dropped support for python 3.3

### Fixed

- For junitxml plugin use test module in place of classname if no classname exists

## 7.7.15 0.7.4 (2018-02-17)

### Added

- Setup tools invocation now handles coverage

### Changed

- Running nose2 via setuptools will now trigger CreateTestsEvent and CreatedTestSuiteEvent

### Fixed

- Respect fail\_under in coverage config
- Avoid infinite recursion when loading setuptools from zipped egg
- Manpage now renders reproducibly
- MP doc build now reproducible

## 7.7.16 0.7.3 (2017-12-13)

### Added

- support for python 3.6.

### Fixed

- Tests failing due to .coveragerc not in MANIFEST

## 7.7.17 0.7.2 (2017-11-14)

Includes changes from version 0.7.1, never released.

### Fixed

- Proper indentation of test with docstring in layers
- MP plugin now calls startSubprocess in subprocess

### Changed

- Add Makefile to enable “quickstart” workflow
- Removed bootstrap.sh and test.sh

### Fixed

- Automatically create .coverage file during coverage reporting
- Better handling of import failures

### 7.7.18 0.7.0 (2017-11-05)

Note: v0.7.0 drops several unsupported python versions

#### Added

- Add layer fixture events and hooks
- junit-xml: add logs in “system-out”
- Give full exc\_info to loader.failedLoadTests

#### Changed

- Replace cov-core with coverage in the coverage plugin
- Give better error when cannot import a testname
- Better errors when tests fail to load
- Allow combination of MP and OutputBuffer plugins on Python 3

#### Removed

- Dropped unsupported Python 2.6, 3.2, 3.3
- nose2.compat is removed because it is no longer needed. If you have `from nose2.compat import unittest` in your code, you will need to replace it with `import unittest`.

#### Fixed

- Prevent crashing from UnicodeDecodeError
- Fix unicode stream encoding

### 7.7.19 0.6.5 (2016-06-29)

#### Added

- Add `nose2.__version__`

### 7.7.20 0.6.4 (2016-03-15)

#### Fixed

- MP will never spawn more processes than there are tests. e.g. When running only one test, only one process is spawned

### 7.7.21 0.6.3 (2016-03-01)

#### Changed

- Add support for python 3.4, 3.5

### 7.7.22 0.6.2 (2016-02-24)

#### Fixed

- fix the coverage plugin tests for coverage==3.7.1

### 7.7.23 0.6.1 (2016-02-23)

#### Fixed

- missing test files added to package.

### 7.7.24 0.6.0 (2016-02-21)

#### Added

- Junit XML report support properties
- Add a *createdTestSuite* event, fired after test loading

#### Changed

- Improve test coverage
- Improve CI
- When test loading fails, print the traceback

#### Fixed

- Junit-xml plugin fixed on windows
- Ensure tests are importable before trying to load them
- Fail test instead of skipping it, when setup fails
- Make the *collect* plugin work with layers
- Fix coverage plugin to take import-time coverage into account

### 7.7.25 0.5.0 (2014-09-14)

#### Added

- *with\_setup* and *with\_teardown* decorators to set the setup & teardown on a function
- *dundertests* plugin to skip tests with *\_\_test\_\_ == False*
- *cartesian\_params* decorator
- coverage plugin
- *EggDiscoveryLoader* for discovering tests within Eggs
- Support *params* with *such*
- Include logging output in junit XML

#### Changed

- *such* errors early if *Layers* plugin is not loaded
- Allow use of *nose2.main()* from within a test module

#### Fixed

- *Such* DSL ignores two *such.A* with the same description
- Record skipped tests as ‘skipped’ instead of ‘skips’
- Result output failed on unicode characters

- Fix multiprocessing plugin on Windows
- Ensure plugins write to the event stream
- multiprocessing could lock master proc and fail to exit
- junit report path was sensitive to changes in cwd
- Test runs would crash if a TestCase `__init__` threw an exception
- Plugin failures no longer crash the whole test run
- Handle errors in test setup and teardown
- Fix reporting of xfail tests
- Log capture was waiting too long to render mutable objects to strings
- Layers plugin was not running testSetUp/testTearDown from higher *such* layers

### 7.7.26 0.4.7 (2013-08-13)

#### Added

- start-dir config option. Thanks to Stéphane Klein.
- Help text for verbose flag. Thanks to Tim Sampson.
- Added badges to README. Thanks to Omer Katz.

#### Changed

- Updated six version requirement to be less Restrictive. Thanks to Stéphane Klein.
- Cleaned up numerous PEP8 violations. Thanks to Omer Katz.

#### Fixed

- Fixed broken import in collector.py. Thanks to Shaun Crampton.
- Fixed processes command line option in mp plugin. Thanks to Tim Sampson.
- Fixed handling of class fixtures in multiprocessing plugin. Thanks to Tim Sampson.
- Fixed intermittent test failure caused by nondeterministic key ordering. Thanks to Stéphane Klein.
- Fixed syntax error in printhooks. Thanks to Tim Sampson.
- Fixed formatting in changelog. Thanks to Omer Katz.
- Fixed typos in docs and examples. Thanks to Tim Sampson.

### 7.7.27 0.4.6 (2013-04-07)

#### Changed

- Docs note support for python 3.3. Thanks Omer Katz for the bug report.

#### Fixed

- Fixed DeprecationWarning for compiler package on python 2.7. Thanks Max Arnold.
- Fixed lack of timing information in junitxml exception reports. Thanks Viacheslav Dukalskiy.
- Cleaned up junitxml xml output. Thanks Philip Thiem.

### 7.7.28 0.4.5 (2012-12-16)

#### Fixed

- Fixed broken interaction between attrib and layers plugins. They can now be used together. Thanks @fajpunk.
- Fixed incorrect calling order of layer setup/teardown and test setup/test teardown methods. Thanks again @fajpunk for tests and fixes.

### 7.7.29 0.4.4 (2012-11-26)

#### Fixed

- Fixed sort key generation for layers.

### 7.7.30 0.4.3 (2012-11-21)

#### Fixed

- Fixed packaging for non-setuptools, pre-python 2.7. Thanks to fajpunk for the patch.

### 7.7.31 0.4.2 (2012-11-19)

#### Added

- Added `uses` method to `such.Scenario` to allow use of externally-defined layers in such DSL tests.

#### Fixed

- Fixed unpredictable ordering of layer tests.

### 7.7.32 0.4.1 (2012-06-18)

Includes changes from version 0.4, never released.

#### Fixed

- Fixed packaging bug.

#### Added

- `nose2.plugins.layers` to support Zope testing style fixture layers.
- `nose2.tools.such`, a spec-like DSL for writing tests with layers.
- `nose2.plugins.loader.loadtests` to support the unittest2 `load_tests` protocol.

### 7.7.33 0.3 (2012-04-15)

#### Added

- `nose2.plugins.mp` to support distributing test runs across multiple processes.
- `nose2.plugins.testclasses` to support loading tests from ordinary classes that are not subclasses of `unittest.TestCase`.
- `nose2.main.PluggableTestProgram` now accepts an `extraHooks` keyword argument, which allows attaching arbitrary objects to the hooks system.



**Changed**

- The default script target was changed from `nose2.main` to `nose2.discover`. The former may still be used for running a single module of tests, unittest-style. The latter ignores the `module` argument. Thanks to @drcaciuc for the bug report (#32).

**Fixed**

- Fixed bug that caused Skip reason to always be set to `None`.

**7.7.34 0.2 (2012-02-06)****Added**

- `nose2.plugins.junitxml` to support jUnit XML output
- `nose2.plugins.attrib` to support test filtering by attributes

**Changed**

- Added `afterTestRun` hook and moved result report output calls to that hook. This prevents plugin ordering issues with the `stopTestRun` hook (which still exists, and fires before `afterTestRun`).

**Fixed**

- Fixed bug in loading of tests by name that caused `ImportErrors` to be silently ignored.
- Fixed missing `__unittest` flag in several modules. Thanks to Wouter Overmeire for the patch.
- Fixed module fixture calls for function, generator and param tests.
- Fixed passing of command-line argument values to list options. Before this fix, lists of lists would be appended to the option target. Now, the option target list is extended with the new values. Thanks to memedough for the bug report.

**7.7.35 0.1 (2012-01-19)**

Initial release.



## PLUGIN DEVELOPER'S GUIDE

### 8.1 Writing Plugins

nose2 supports plugins for test collection, selection, observation and reporting – among other things. There are two basic rules for plugins:

- Plugin classes must subclass `nose2.events.Plugin`.
- Plugins may implement any of the methods described in the *Hook reference*.

#### 8.1.1 Hello World

Here's a basic plugin. It doesn't do anything besides log a message at the start of a test run.

```
import logging
import os

from nose2.events import Plugin

log = logging.getLogger('nose2.plugins.helloworld')

class HelloWorld(Plugin):
    configSection = 'helloworld'
    commandLineSwitch = (None, 'hello-world', 'Say hello!')

    def startTestRun(self, event):
        log.info('Hello pluginized world!')
```

To see this plugin in action, save it into an importable module, then add that module to the `plugins` key in the `[unittest]` section of a config file loaded by nose2, such as `unittest.cfg`. Then run nose2:

```
nose2 --log-level=INFO --hello-world
```

And you should see the log message before the first dot appears.

#### 8.1.2 Loading plugins

As mentioned above, for nose2 to find a plugin, it must be in an importable module, and the module must be listed under the `plugins` key in the `[unittest]` section of a config file loaded by nose2:

```
[unittest]
plugins = mypackage.someplugin
```

(continues on next page)

(continued from previous page)

```
otherpackage.thatplugin
thirdpackage.plugins.metoo
```

As you can see, plugin *modules* are listed, one per line. All plugin classes in those modules will be loaded – but not necessarily active. Typically plugins do not activate themselves (“register”) without seeing a command-line flag, or `always-on = True` in their config file section.

### 8.1.3 Command-line Options

nose2 uses `argparse` for command-line argument parsing. Plugins may enable command-line options that register them as active, or take arguments or flags controlling their operation.

The most basic thing to do is to set the plugin’s `commandLineSwitch` attribute, which will automatically add a command-line flag that registers the plugin.

To add other flags or arguments, you can use the Plugin methods `nose2.events.Plugin.addFlag()`, `nose2.events.Plugin.addArgument()` or `nose2.events.Plugin.addOption()`. If those don’t offer enough flexibility, you can directly manipulate the argument parser by accessing `self.session.argparse` or the plugin option group by accessing `self.session.pluginargs`.

Please note though that the *majority* of your plugin’s configuration should be done via config file options, not command line options.

### 8.1.4 Config File Options

Plugins may specify a config file section that holds their configuration by setting their `configSection` attribute. All plugins, regardless of whether they specify a config section, have a `config` attribute that holds a `nose2.config.Config` instance. This will be empty of values if the plugin does not specify a config section or if no loaded config file includes that section.

Plugins should extract the user’s configuration selections from their `config` attribute in their `__init__` methods. Plugins that want to use nose2’s `Sphinx` extension to automatically document themselves **must** do so.

Config file options may be extracted as strings, ints, booleans or lists.

You should provide reasonable defaults for all config options.

### 8.1.5 Guidelines

#### Events

nose2’s plugin API is based on the API in unittest2’s `plugins` branch (under-development). It differs from nose’s in one major area: what it passes to hooks. Where nose passes a variety of arguments, nose2 *always passes an event*. The events are listed in the [Event reference](#).

Here’s the key thing about that: *event attributes are read-write*. Unless stated otherwise in the documentation for a hook, you can set a new value for any event attribute, and *this will do something*. Plugins and nose2 systems will see that new value and either use it instead of what was originally set in the event (example: the reporting stream or test executor), or use it to supplement something they find elsewhere (example: `extraTests` on a test loading event).

#### “Handling” events

Many hooks give plugins a chance to completely handle events, bypassing other plugins and any core nose2 operations. To do this, a plugin sets `event.handled` to `True` and, generally, returns an appropriate value from the hook method. What is an appropriate value varies by hook, and some hooks *can’t* be handled in this way. But even for hooks where handling the event doesn’t stop all processing, it *will* stop subsequently-loaded plugins from seeing the event.

## Logging

nose2 uses the logging classes from the standard library. To enable users to view debug messages easily, plugins should use `logging.getLogger()` to acquire a logger in the `nose2.plugins` namespace.

### 8.1.6 Recipes

- Writing a plugin that monitors or controls test result output

Implement any of the `report*` hook methods, especially if you want to output to the console. If outputting to file or other system, you might implement `testOutcome()` instead.

Example: `nose2.plugins.result.ResultReporter`

- Writing a plugin that handles exceptions

If you just want to handle some exceptions as skips or failures instead of errors, see `nose2.plugins.outcomes.Outcomes`, which offers a simple way to do that. Otherwise, implement `setTestOutcome()` to change test outcomes.

Example: `nose2.plugins.outcomes.Outcomes`

- Writing a plugin that adds detail to error reports

Implement `testOutcome()` and put your extra information into `event.metadata`, then implement `outcomeDetail()` to extract it and add it to the error report.

Examples: `nose2.plugins.buffer.OutputBufferPlugin`, `nose2.plugins.logcapture.LogCapture`

- Writing a plugin that loads tests from files other than python modules

Implement `handleFile()`.

Example: `nose2.plugins.doctests.DocTestLoader`

- Writing a plugin that loads tests from python modules

Implement at least `loadTestsFromModule()`.

#### Warning

One thing to beware of here is that if you return tests as dynamically-generated test cases, or instances of a testcase class that is defined *anywhere* but the module being loaded, you *must* use `nose2.util.transplant_class()` to make the test case class appear to have originated in that module. Otherwise, module-level fixtures will not work for that test, and may be ignored entirely for the module if there are no test cases that are or appear to be defined there.

- Writing a plugin that prints a report

Implement `beforeErrorList()`, `beforeSummaryReport()` or `afterSummaryReport()`

Example: `nose2.plugins.prof.Profiler`

- Writing a plugin that selects or rejects tests

Implement `matchPath` or `getTestCaseNames`.

Example: `nose2.plugins.loader.parameters.Parameters`

## 8.2 Documenting plugins

You should do it. Nobody will use your plugins if you don't. Or if they do use them, they will curse you whenever things go wrong.

One easy way to document your plugins is to use nose2's [Sphinx](#) extension, which provides an `autoplugin` directive that will produce decent reference documentation from your plugin classes.

To use it, add `nose2.sphinxext` to the `extensions` list in the `conf.py` file in your docs directory.

Then add an `autoplugin` directive to a `*.rst` file, like this:

```
.. autoplugin :: mypackage.plugins.PluginClass
```

This will produce output that includes the config vars your plugin loads in `__init__`, as well as any command line options your plugin registers. This is why you *really* should extract config vars and register command-line options in `__init__`.

The output will also include an `autoclass` section for your plugin class, so you can put more narrative documentation in the plugin's docstring for users to read.

Of course you can, and should, write some words before the reference docs explaining what your plugin does and how to use it. You can put those words in the `*.rst` file itself, or in the docstring of the module where your plugin lives.

## 8.3 Event reference

**class** `nose2.events.CommandLineArgsEvent`(*args*, *\*\*kw*)

Event fired after parsing of command line arguments.

Plugins can respond to this event by configuring themselves or other plugins or modifying the parsed arguments.

### Note

Many plugins register options with callbacks. By the time this event fires, those callbacks have already fired. So you can't use this event to reliably influence all plugins.

### **args**

Args object returned by `argparse`.

**class** `nose2.events.CreateTestsEvent`(*loader*, *testNames*, *module*, *\*\*kw*)

Event fired before test loading.

Plugins can take over test loading by returning a test suite and setting `handled` on this event.

### **loader**

Test loader instance

### **names**

List of test names. May be empty or `None`.

### **module**

Module to load from. May be `None`. If not `None`, names should be considered relative to this module.

**class** `nose2.events.CreatedTestSuiteEvent`(*suite*, *\*\*kw*)

Event fired after test loading.

Plugins can replace the loaded test suite by returning a test suite and setting `handled` on this event.

**suite**

Test Suite instance

**class** nose2.events.**DescribeTestEvent**(*test, description=None, errorList=False, \*\*kw*)

Event fired to get test description.

**test**

The test case

**description**

Description of the test case. Plugins can set this to change how tests are described in output to users.

**errorList**

Is the event fired as part of error list output?

**class** nose2.events.**Event**(*\*\*metadata*)

Base class for all events.

**metadata**

Storage for arbitrary information attached to an event.

**handled**

Set to True to indicate that a plugin has handled the event, and no other plugins or core systems should process it further.

**version**

Version of the event API. This will be incremented with each release of nose2 that changes the API.

**version** = '0.4'

**class** nose2.events.**GetTestCaseNamesEvent**(*loader, testCase, isTestMethod, \*\*kw*)

Event fired to find test case names in a test case.

Plugins may return a list of names and set **handled** on this event to force test case name selection.

**loader**

Test loader instance

**testCase**

The unittest.TestCase instance being loaded.

**testMethodPrefix**

Set this to change the test method prefix. Unless set by a plugin, it is None.

**extraNames**

A list of extra test names to load from the test case. To cause extra tests to be loaded from the test case, append the names to this list. Note that the names here must be attributes of the test case.

**excludedNames**

A list of names to exclude from test loading. Add names to this list to prevent other plugins from loading the named tests.

**isTestMethod**

Callable that plugins can use to examine test case attributes to determine whether nose2 thinks they are test methods.

**class** nose2.events.**HandleFileEvent**(*loader, name, path, pattern, topLevelDirectory, \*\*kw*)

Event fired when a non-test file is examined.

**Note**

This event is fired for all processed python files and modules including but not limited to the ones that match the test file pattern.

**loader**

Test loader instance

**name**

File basename

**path**

Full path to file

**pattern**

Current test file match pattern

**topLevelDirectory**

Top-level directory of the test run

**extraTests**

A list of extra tests loaded from the file. To load tests from a file without interfering with other plugins' loading activities, append tests to extraTests.

Plugins may set **handled** on this event and return a test suite to prevent other plugins from loading tests from the file. If any plugin sets **handled** to **True**, **extraTests** will be ignored.

**class** nose2.events.**LoadFromModuleEvent**(*loader, module, \*\*kw*)

Event fired when a test module is loaded.

**loader**

Test loader instance

**module**

The module whose tests are to be loaded

**extraTests**

A list of extra tests loaded from the module. To load tests from a module without interfering with other plugins' loading activities, append tests to extraTests.

Plugins may set **handled** on this event and return a test suite to prevent other plugins from loading tests from the module. If any plugin sets **handled** to **True**, **extraTests** will be ignored.

**class** nose2.events.**LoadFromNameEvent**(*loader, name, module, \*\*kw*)

Event fired to load tests from test names.

**loader**

Test loader instance

**name**

Test name to load

**module**

Module to load from. May be **None**. If not **None**, names should be considered relative to this module.



**extraTests**

A list of extra tests loaded from the name. To load tests from a test name without interfering with other plugins' loading activities, append tests to extraTests.

Plugins may set `handled` on this event and return a test suite to prevent other plugins from loading tests from the test name. If any plugin sets `handled` to `True`, `extraTests` will be ignored.

**class** nose2.events.**LoadFromNamesEvent**(*loader, names, module, \*\*kw*)

Event fired to load tests from test names.

**loader**

Test loader instance

**names**

List of test names. May be empty or `None`.

**module**

Module to load from. May be `None`. If not `None`, names should be considered relative to this module.

**extraTests**

A list of extra tests loaded from the tests named. To load tests from test names without interfering with other plugins' loading activities, append tests to extraTests.

Plugins may set `handled` on this event and return a test suite to prevent other plugins from loading tests from the test names. If any plugin sets `handled` to `True`, `extraTests` will be ignored.

**class** nose2.events.**LoadFromTestCaseEvent**(*loader, testCase, \*\*kw*)

Event fired when tests are loaded from a test case.

**loader**

Test loader instance

**testCase**

The `unittest.TestCase` instance being loaded.

**extraTests**

A list of extra tests loaded from the module. To load tests from a test case without interfering with other plugins' loading activities, append tests to extraTests.

Plugins may set `handled` on this event and return a test suite to prevent other plugins from loading tests from the test case. If any plugin sets `handled` to `True`, `extraTests` will be ignored.

**class** nose2.events.**MatchPathEvent**(*name, path, pattern, \*\*kw*)

Event fired during file matching.

Plugins may return `False` and set `handled` on this event to prevent a file from being matched as a test file, regardless of other system settings.

**path**

Full path to the file

**name**

File basename

**pattern**

Current test file match pattern

**class** nose2.events.**ModuleSuiteEvent**(*loader, module, suite, \*\*kw*)

**class** nose2.events.**OutcomeDetailEvent**(*outcomeEvent*, *\*\*kw*)

Event fired to acquire additional details about test outcome.

**outcomeEvent**

A *nose2.events.TestOutcomeEvent* instance holding the test outcome to be described.

**extraDetail**

Extra detail lines to be appended to test outcome output. Plugins can append lines (of strings) to this list to include their extra information in the error list report.

**class** nose2.events.**PluginsLoadedEvent**(*pluginsLoaded*, *\*\*kw*)

Event fired after all plugin classes are loaded.

**pluginsLoaded**

List of all loaded plugin classes

**class** nose2.events.**ReportSummaryEvent**(*stopTestEvent*, *stream*, *reportCategories*, *\*\*kw*)

Event fired before and after summary report.

**stopTestEvent**

A *nose2.events.StopTestEvent* instance.

**stream**

The output stream. Plugins can set this to change or capture output.

**reportCategories**

Dictionary of report category and test events captured in that category. Default categories include ‘errors’, ‘failures’, ‘skipped’, ‘expectedFails’, and ‘unexpectedSuccesses’. Plugins may add their own categories.

**class** nose2.events.**ReportTestEvent**(*testEvent*, *stream*, *\*\*kw*)

Event fired to report a test event.

Plugins can respond to this event by producing output for the user.

**testEvent**

A test event. In most cases, a *nose2.events.TestOutcomeEvent* instance. For startTest, a *nose2.events.StartTestEvent* instance.

**stream**

The output stream. Plugins can set this to change or capture output.

**class** nose2.events.**ResultCreatedEvent**(*result*, *\*\*kw*)

Event fired when test result handler is created.

**result**

Test result handler instance. Plugins may replace the test result by setting this attribute to a new test result instance.

**class** nose2.events.**ResultStopEvent**(*result*, *shouldStop*, *\*\*kw*)

Event fired when a test run is told to stop.

Plugins can use this event to prevent other plugins from stopping a test run.

**result**

Test result

**shouldStop**

Set to True to indicate that the test run should stop.

**class** nose2.events.**ResultSuccessEvent**(*result*, *success*, *\*\*kw*)

Event fired at end of test run to determine success.

This event fires at the end of the test run and allows plugins to determine whether the test run was successful.

**result**

Test result

**success**

Set this to True to indicate that the test run was successful. If no plugin sets the **success** to True, the test run fails. Should be initialized to None to indicate that the status has not been set yet (so that plugins can always differentiate an explicit failure in an earlier hook from no pass/fail status having been set yet).

**class** nose2.events.**RunnerCreatedEvent**(*runner*, *\*\*kw*)

Event fired when test runner is created.

**runner**

Test runner instance. Plugins may replace the test runner by setting this attribute to a new test runner instance.

**class** nose2.events.**StartLayerSetupEvent**(*layer*, *\*\*kw*)

Event fired before running a layer setup.

**layer**

The current layer instance, for which setup is about to run.

**class** nose2.events.**StartLayerSetupTestEvent**(*layer*, *test*, *\*\*kw*)

Event fired before test cases setups in layers.

**layer**

The current layer instance.

**test**

The test instance for which the setup is about to run.

**class** nose2.events.**StartLayerTeardownEvent**(*layer*, *\*\*kw*)

Event fired before running a layer teardown.

**layer**

The current layer instance, for which teardown is about to run.

**class** nose2.events.**StartLayerTeardownTestEvent**(*layer*, *test*, *\*\*kw*)

Event fired before test cases teardowns in layers.

**layer**

The current layer instance.

**test**

The test instance for which teardown is about to run.

**class** nose2.events.**StartTestEvent**(*test*, *result*, *startTime*, *\*\*kw*)

Event fired before a test is executed.

**test**

The test case

**result**

Test result

**startTime**

Timestamp of test start

**class** nose2.events.**StartTestRunEvent**(*runner, suite, result, startTime, executeTests, \*\*kw*)

Event fired when test run is about to start.

Test collection is complete before this event fires, but no tests have yet been executed.

**runner**

Test runner

**suite**

Top-level test suite to execute. Plugins can filter this suite, or set event.suite to change which tests execute (or how they execute).

**result**

Test result

**startTime**

Timestamp of test run start

**executeTests**

Callable that will be used to execute tests. Plugins may set this attribute to wrap or otherwise change test execution. The callable must match the signature:

```
def execute(suite, result):  
    ...
```

To prevent normal test execution, plugins may set **handled** on this event to **True**. When **handled** is true, the test executor does not run at all.

**class** nose2.events.**StopLayerSetupEvent**(*layer, \*\*kw*)

Event fired after running a layer setup.

**layer**

The current layer instance, for which setup just ran.

**class** nose2.events.**StopLayerSetupTestEvent**(*layer, test, \*\*kw*)

Event fired after test cases setups in layers.

**layer**

The current layer instance.

**test**

The test instance for which the setup just finished.

**class** nose2.events.**StopLayerTeardownEvent**(*layer, \*\*kw*)

Event fired after running a layer teardown.

**layer**

The current layer instance, for which teardown just ran.

**class** nose2.events.**StopLayerTeardownTestEvent**(*layer, test, \*\*kw*)

Event fired after test cases teardowns in layers.

**layer**

The current layer instance.

**test**

The test instance for which teardown just ran.

**class** nose2.events.**StopTestEvent**(*test, result, stopTime, \*\*kw*)

Event fired after a test is executed.

**test**

The test case

**result**

Test result

**stopTime**

Timestamp of test stop

**class** nose2.events.**StopTestRunEvent**(*runner, result, stopTime, timeTaken, \*\*kw*)

Event fired when test run has stopped.

**runner**

Test runner

**result**

Test result

**stopTime**

Timestamp of test run stop

**timeTaken**

Number of seconds test run took to execute

**class** nose2.events.**TestOutcomeEvent**(*test, result, outcome, exc\_info=None, reason=None, expected=False, shortLabel=None, longLabel=None, \*\*kw*)

Event fired when a test completes.

**test**

The test case

**result**

Test result

**outcome**

Description of test outcome. Typically will be one of 'error', 'failed', 'skipped', 'passed', or 'subtest'.

**exc\_info**

If the test resulted in an exception, the tuple of (exception class, exception value, traceback) as returned by `sys.exc_info()`. If the test did not result in an exception, `None`.

**reason**

For test outcomes that include a reason (Skips, for example), the reason.

**expected**

Boolean indicating whether the test outcome was expected. In general, all tests are expected to pass, and any other outcome will have expected as `False`. The exceptions to that rule are unexpected successes and expected failures.

**shortLabel**

A short label describing the test outcome. (For example, 'E' for errors).

**longLabel**

A long label describing the test outcome (for example, 'ERROR' for errors).

Plugins may influence how the rest of the system sees the test outcome by setting `outcome` or `exc_info` or `expected`. They may influence how the test outcome is reported to the user by setting `shortLabel` or `longLabel`.

**class** `nose2.events.UserInteractionEvent(**kw)`

Event fired before and after user interaction.

Plugins that capture stdout or otherwise prevent user interaction should respond to this event.

To prevent the user interaction from occurring, return `False` and set `handled`. Otherwise, turn off whatever you are doing that prevents users from typing/clicking/touching/psionics/whatever.

## 8.4 Hook reference

Note
Hooks are listed here in order of execution.

### 8.4.1 Pre-registration Hooks

**pluginsLoaded**(*self*, *event*)

**Parameters**

**event** – `nose2.events.PluginsLoadedEvent`

The `pluginsLoaded` hook is called after all config files have been read, and all plugin classes loaded. Plugins that register automatically (those that call `nose2.events.Plugin.register()` in `__init__` or have `always-on = True` set in their config file sections) will have already been registered with the hooks they implement. Plugins waiting for command-line activation will not yet be registered.

Plugins can use this hook to examine or modify the set of loaded plugins, inject their own hook methods using `nose2.events.PluginInterface.addMethod()`, or take other actions to set up or configure themselves or the test run.

Since `pluginsLoaded` is a pre-registration hook, it is called for *all plugins* that implement the method, whether they have registered or not. Plugins that do not automatically register themselves should limit their actions in this hook to configuration, since they may not actually be active during the test run.

**handleArgs**(*self*, *event*)

**Parameters**

**event** – `nose2.events.CommandLineArgsEvent`

The `handleArgs` hook is called after all arguments from the command line have been parsed. Plugins can use this hook to handle command-line arguments in non-standard ways. They should not use it to try to modify arguments seen by other plugins, since the order in which plugins execute in a hook is not guaranteed.

Since `handleArgs` is a pre-registration hook, it is called for *all plugins* that implement the method, whether they have registered or not. Plugins that do not automatically register themselves should limit their actions in this hook to configuration, since they may not actually be active during the test run.

## 8.4.2 Standard Hooks

These hooks are called for registered plugins only.

**createTests**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.CreateTestsEvent` instance

Plugins can take over test loading by returning a test suite and setting `event.handled` to `True`.

**loadTestsFromNames**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.LoadFromNamesEvent` instance

Plugins can return a test suite or list of test suites and set `event.handled` to `True` to prevent other plugins from loading tests from the given names, or append tests to `event.extraTests`. Plugins can also remove names from `event.names` to prevent other plugins from acting on those names.

**loadTestsFromName**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.LoadFromNameEvent` instance

Plugins can return a test suite and set `event.handled` to `True` to prevent other plugins from loading tests from the given name, or append tests to `event.extraTests`.

**handleFile**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.HandleFileEvent` instance

Plugins can use this hook to load tests from files that are not Python modules. Plugins may either append tests to `event.extraTest`, or, if they want to prevent other plugins from processing the file, set `event.handled` to `True` and return a test case or test suite.

**matchPath**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.MatchPathEvent` instance

Plugins can use this hook to prevent python modules from being loaded by the test loader or force them to be loaded by the test loader. Set `event.handled` to `True` and return `False` to cause the loader to skip the module. Set `event.handled` to `True` and return `True` to cause the loader to load the module.

**loadTestsFromModule**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.LoadFromModuleEvent` instance

Plugins can use this hook to load tests from test modules. To prevent other plugins from loading from the module, set `event.handled` and return a test suite. Plugins can also append tests to `event.extraTests` – usually that's what you want to do, since that will allow other plugins to load their tests from the module as well.

See also [this warning](#) about test cases not defined in the module.

**loadTestsFromTestCase**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.LoadFromTestCaseEvent` instance

Plugins can use this hook to load tests from a `unittest.TestCase`. To prevent other plugins from loading tests from the test case, set `event.handled` to `True` and return a test suite. Plugins can also append tests to `event.extraTests` – usually that’s what you want to do, since that will allow other plugins to load their tests from the test case as well.

**getTestCaseNames**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.GetTestCaseNamesEvent` instance

Plugins can use this hook to limit or extend the list of test case names that will be loaded from a `unittest.TestCase` by the standard nose2 test loader plugins (and other plugins that respect the results of the hook). To force a specific list of names, set `event.handled` to `True` and return a list: this exact list will be the only test case names loaded from the test case. Plugins can also extend the list of names by appending test names to `event.extraNames`, and exclude names by appending test names to `event.excludedNames`.

**runnerCreated**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.RunnerCreatedEvent` instance

Plugins can use this hook to wrap, capture or replace the test runner. To replace the test runner, set `event.runner`.

**resultCreated**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ResultCreatedEvent` instance

Plugins can use this hook to wrap, capture or replace the test result. To replace the test result, set `event.result`.

**startTestRun**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartTestRunEvent` instance

Plugins can use this hook to take action before the start of the test run, and to replace or wrap the test executor. To replace the executor, set `event.executeTests`. This must be a callable that takes two arguments: the top-level test and the test result.

To prevent the test executor from running at all, set `event.handled` to `True`.

**startLayerSetup**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartLayerSetupEvent` instance (only available in suites with layers).

Plugins can use this hook to take action before the start of the `setUp` in a layer.

**stopLayerSetup**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopLayerSetupEvent` instance (only available in suites with layers).

Plugins can use this hook to take action after `setUp` finishes, in a layer.

**startLayerSetupTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartLayerSetupTestEvent` instance (only available in suites with layers).



Plugins can use this hook to take action before the start of `testSetUp` in a layer.

**stopLayerSetupTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopLayerSetupTestEvent` instance (only available in suites with layers).

Plugins can use this hook to take action after `testSetUp` finishes, in a layer.

**startTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartTestEvent` instance

Plugins can use this hook to take action immediately before a test runs.

**reportStartTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to produce output for the user at the start of a test. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**describeTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.DescribeTestEvent` instance

Plugins can use this hook to alter test descriptions. To return a nonstandard description for a test, set `event.description`. Be aware that other plugins may have set this also!

**setTestOutcome**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.TestOutcomeEvent` instance

Plugins can use this hook to alter test outcomes. Plugins can `event.outcome` to change the outcome of the event, tweak, change or remove `event.exc_info`, set or clear `event.expected`, and so on.

**testOutcome**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.TestOutcomeEvent` instance

Plugins can use this hook to take action based on the outcome of tests. Plugins *must not* alter test outcomes in this hook: that's what `setTestOutcome()` is for. Here, plugins may only react to the outcome event, not alter it.

**reportSuccess**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.LoadFromNamesEvent` instance

Plugins can use this hook to report test success to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportError**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report a test error to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportFailure**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report test failure to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportSkip**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report a skipped test to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportExpectedFailure**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report an expected failure to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportUnexpectedSuccess**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report an unexpected success to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

**reportOtherOutcome**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportTestEvent` instance

Plugins can use this hook to report a custom test outcome to the user. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console. To prevent other plugins from reporting to the user, set `event.handled` to `True`.

`nose2` will never produce this event by itself. It only gets triggered if a plugin creates a test result with an unrecognized outcome.

**stopTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopTestEvent` instance

Plugins can use this hook to take action after a test has completed running and reported its outcome.

**startLayerTeardownTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartLayerTeardownTestEvent` instance (only available in suites with layers).

Plugins can use this hook to take action before the start of `testTearDown()` in a layer.

**stopLayerTeardownTest**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopLayerTeardownTestEvent` instance (only available in suites with layers).

Plugins can use this hook to take action after `testTearDown()` finishes, in a layer.

**startLayerTeardown**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StartLayerTeardownEvent` instance (only available in suites with layers).

Plugins can use this hook to take action before the start of the `tearDown()` in a layer.

**stopLayerTeardown**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopLayerTeardownEvent` instance (only available in suites with layers).

Plugins can use this hook to take action after `tearDown()` finishes, in a layer.

**stopTestRun**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopTestRunEvent` instance

Plugins can use this hook to take action at the end of a test run.

**afterTestRun**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.StopTestRunEvent` instance

**Note**

New in version 0.2

Plugins can use this hook to take action *after* the end of a test run, such as printing summary reports like the builtin result reporter plugin `nose2.plugins.result.ResultReporter`.

**resultStop**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ResultStopEvent` instance

Plugins can use this hook to *prevent* other plugins from stopping a test run. This hook fires when something calls `nose2.result.PluggableTestResult.stop()`. If you want to prevent this from stopping the test run, set `event.shouldStop` to `False`.

**beforeErrorList**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportSummaryEvent` instance

Plugins can use this hook to output or modify summary information before the list of errors and failures is output. To modify the categories of outcomes that will be reported, plugins can modify the `event.reportCategories` dictionary. Plugins can set, wrap, or capture the output stream by reading or setting `event.stream`. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console.

**outcomeDetail**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.OutcomeDetailEvent` instance

Plugins can use this hook to add additional elements to error list output. Append extra detail lines to `event.extraDetail`; these will be joined together with newlines before being output as part of the detailed error/failure message, after the traceback.

**beforeSummaryReport**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportSummaryEvent` instance

Plugins can use this hook to output or modify summary information before the summary lines are output. To modify the categories of outcomes that will be reported in the summary, plugins can modify the `event.reportCategories` dictionary. Plugins can set, wrap or capture the output stream by reading or setting `event.stream`. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console.

**wasSuccessful**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ResultSuccessEvent` instance

Plugins can use this hook to mark a test run as successful or unsuccessful. If not plugin marks the run as successful, the default state is failure. To mark a run as successful, set `event.success` to `True`. Be ware that other plugins may set this attribute as well!

**afterSummaryReport**(*self*, *event*)

**Parameters**

**event** – A `nose2.events.ReportSummaryEvent` instance

Plugins can use this hook to output a report to the user after the summary line is output. If you want to print to the console, write to `event.stream`. Remember to respect `self.session.verbosity` when printing to the console.

### 8.4.3 User Interaction Hooks

These hooks are called when plugins want to interact with the user.

**beforeInteraction**(*event*)

**Parameters**

**event** – A `nose2.events.UserInteractionEvent`

Plugins should respond to this hook by getting out of the way of user interaction, if the need to, or setting `event.handled` and returning `False`, if they need to but can't.

**afterInteraction**(*event*)

**Parameters**

**event** – A `nose2.events.UserInteractionEvent`

Plugins can respond to this hook by going back to whatever they were doing before the user stepped in and started poking around.

## 8.5 Session reference

### 8.5.1 Session

In nose2, all configuration for a test run is encapsulated in a `Session` instance. Plugins always have the session available as `self.session`.

#### **class** `nose2.session.Session`

Configuration session.

Encapsulates all configuration for a given test run.

#### **argparse**

An instance of `argparse.ArgumentParser`. Plugins can use this directly to add arguments and argument groups, but *must* do so in their `__init__` methods.

#### **pluginargs**

The argparse argument group in which plugins (by default) place their command-line arguments. Plugins can use this directly to add arguments, but *must* do so in their `__init__` methods.

#### **hooks**

The `nose2.events.PluginInterface` instance contains all available plugin methods and hooks.

#### **plugins**

The list of loaded – but not necessarily *active* – plugins.

#### **verbosity**

Current verbosity level. Default: 1.

#### **startDir**

Start directory of test run. Test discovery starts here. Default: current working directory.

#### **topLevelDir**

Top-level directory of test run. This directory is added to `sys.path`. Default: starting directory.

#### **libDirs**

Names of code directories, relative to starting directory. Default: ['lib', 'src']. These directories are added to `sys.path` and discovery if they exist.

#### **testFilePattern**

Pattern used to discover test module files. Default: `test*.py`

#### **testMethodPrefix**

Prefix used to discover test methods and functions: Default: 'test'.

#### **unittest**

The config section for nose2 itself.

#### **configClass**

alias of `Config`

#### **get**(*section*)

Get a config section.

**Parameters**

**section** – The section name to retrieve.

**Returns**

instance of `self.configClass`.

**isPluginLoaded**(*pluginName*)

Returns True if a given plugin is loaded.

**Parameters**

**pluginName** – the name of the plugin module: e.g. “nose2.plugins.layers”.

**loadConfigFiles**(\**filenames*)

Load config files.

**Parameters**

**filenames** – Names of config files to load.

Loads all names files that exist into `self.config`.

**loadPlugins**(*modules=None, exclude=None*)

Load plugins.

**Parameters**

**modules** – List of module names from which to load plugins.

**loadPluginsFromModule**(*module*)

Load plugins from a module.

**Parameters**

**module** – A python module containing zero or more plugin classes.

**prepareSysPath**()

Add code directories to `sys.path`

**registerPlugin**(*plugin*)

Register a plugin.

**Parameters**

**plugin** – A `nose2.events.Plugin` instance.

Register the plugin with all methods it implements.

**setStartDir**(*args\_start\_dir=None*)

start dir comes from config and may be overridden by an argument

**setVerbosity**(*args\_verbosity, args\_verbose, args\_quiet*)

Determine verbosity from various (possibly conflicting) sources of info

**Parameters**

- **args\_verbosity** – The `-verbosity` argument value
- **args\_verbose** – count of `-v` options
- **args\_quiet** – count of `-q` options

start with config, override with any given `-verbosity`, then adjust up/down with `-vvv -qq`, etc

## 8.5.2 Config

Configuration values loaded from config file sections are made available to plugins in `Config` instances. Plugins that set `configSection` will have a `Config` instance available as `self.config`.

**class** `nose2.config.Config(items)`

Configuration for a plugin or other entities.

Encapsulates configuration for a single plugin or other element. Corresponds to a `ConfigParser.Section` but provides an extended interface for extracting items as a certain type.

**as\_bool**(*key, default=None*)

Get key value as boolean

1, t, true, on, yes and y (case insensitive) are accepted as `True` values. All other values are `False`.

**as\_float**(*key, default=None*)

Get key value as float

**as\_int**(*key, default=None*)

Get key value as integer

**as\_list**(*key, default=None*)

Get key value as list.

The value is split into lines and returned as a list. Lines are stripped of whitespace, and lines beginning with `#` are skipped.

**as\_str**(*key, default=None*)

Get key value as str

**get**(*key, default=None*)

Get key value

## 8.6 Plugin class reference

The plugin system in nose2 is based on the plugin system in unittest2's `plugins` branch.

### 8.6.1 Plugin base class

**class** `nose2.events.Plugin(*args, **kwargs)`

Base class for nose2 plugins

All nose2 plugins must subclass this class.

**session**

The `nose2.session.Session` under which the plugin has been loaded.

**config**

The `nose2.config.Config` representing the plugin's config section as loaded from the session's config files.

**commandLineSwitch**

A tuple of (short opt, long opt, help text) that defines a command line flag that activates this plugin. The short opt may be `None`. If defined, it must be a single upper-case character. Both short and long opt must *not* start with dashes.

Example:

```
commandLineSwitch = ('B', 'buffer-output', 'Buffer output during
tests')
```

**configSection**

The name config file section to load into this plugin's config.

**alwaysOn**

If this plugin should automatically register itself, set `alwaysOn` to `True`. Default is `False`.

**Note**

Plugins that use config values from config files and want to use the nose2 sphinx extension to automatically generate documentation *must* extract all config values from `self.config` in `__init__`. Otherwise the extension will not be able to detect the config keys that the plugin uses.

**addArgument**(*callback, short\_opt, long\_opt, help\_text=None*)

Add command-line option that takes one argument.

**Parameters**

- **callback** – Callback function to run when flag is seen. The callback will receive one argument.
- **short\_opt** – Short option. Must be uppercase, no dashes.
- **long\_opt** – Long option. Must not start with dashes
- **help\_text** – Help text for users so they know what this flag does.

**addFlag**(*callback, short\_opt, long\_opt, help\_text=None*)

Add command-line flag that takes no arguments

**Parameters**

- **callback** – Callback function to run when flag is seen. The callback will receive one empty argument.
- **short\_opt** – Short option. Must be uppercase, no dashes.
- **long\_opt** – Long option. Must not start with dashes
- **help\_text** – Help text for users so they know what this flag does.

**addMethods**(*\*methods*)

Add new plugin methods to hooks registry

Any plugins that are already registered and implement a method added here will be registered for that method as well.

**addOption**(*callback, short\_opt, long\_opt, help\_text=None, nargs=0*)

Add command-line option.

**Parameters**

- **callback** – Callback function to run when flag is seen. The callback will receive one argument. The “callback” may also be a list, in which case values submitted on the command line will be appended to the list.
- **short\_opt** – Short option. Must be uppercase, no dashes.
- **long\_opt** – Long option. Must not start with dashes



- **help\_text** – Help text for users so they know what this flag does.
- **nargs** – Number of arguments to consume from command line.

**register()**

Register with appropriate hooks.

This activates the plugin and enables it to receive events.

## 8.6.2 Plugin interface classes

**class nose2.events.PluginInterface**

Definition of plugin interface.

Instances of this class contain the methods that may be called, and a dictionary of *nose2.events.Hook* instances bound to each method.

In a plugin, PluginInterface instance is typically available as `self.session.hooks`, and plugin hooks may be called on it directly:

```
event = events.LoadFromModuleEvent(module=the_module)
self.session.hooks.loadTestsFromModule(event)
```

**preRegistrationMethods**

Tuple of methods that are called before registration.

**methods**

Tuple of available plugin hook methods.

**hookClass**

Class to instantiate for each hook. Default: *nose2.events.Hook*.

**addMethod(method)**

Add a method to the available method.

This allows plugins to register for this method.

**Parameters**

**method** – A method name

**hookClass**

alias of *Hook*

**register(method, plugin)**

Register a plugin for a method.

**Parameters**

- **method** – A method name
- **plugin** – A plugin instance

**class nose2.events.Hook(method)**

A plugin hook

Each plugin method in the *nose2.events.PluginInterface* is represented at runtime by a Hook instance that lists the plugins that should be called by that hook.

**method**

The name of the method that this Hook represents.

**plugins**

The list of plugin instances bound to this hook.

## DEVELOPER'S GUIDE

## 9.1 Contributing to nose2

Please do!

### 9.1.1 The Basics

nose2 is hosted on [github](#) and uses GitHub for issue tracking.

Please report issues and make feature requests here: <https://github.com/nose-devs/nose2/issues>

### 9.1.2 Code Contributions

The main rule is: *code changes should include tests*.

If you aren't sure how to add tests, or you don't know why existing tests fail on your changes, that's okay! Submit your patch and ask for help testing it.

#### Local Dev Requirements

To run the tests you must have [tox](#) installed.

Optional but useful tools include [make](#) and [pre-commit](#).

#### Running Tests

To run all tests:

```
$ tox
```

To run linting checks:

```
$ tox -e lint
```

You can also use `make test` and `make lint` for these.

#### Linting

nose2 uses [black](#) and [ruff](#) to enforce code formatting and linting and [pre-commit](#) to run these tools.

For the best development experience, we recommend setting up integrations with your editor and git.

Running [pre-commit](#) as a git hook is optional. To configure it, you must have [pre-commit](#) installed and run:

```
$ pre-commit install
```

**Note**

If you need to bypass pre-commit hooks after setting this up, you can commit with `--no-verify`

## 9.2 Internals

Reference material for things you probably only need to care about if you want to contribute to nose2.

### 9.2.1 nose2.main

**class** nose2.main.PluggableTestProgram(\*\*kw)

TestProgram that enables plugins.

Accepts the same parameters as `unittest.TestProgram`, but most of them are ignored as their functions are handled by plugins.

**Parameters**

- **module** – Module in which to run tests. Default: `__main__()`
- **defaultTest** – Default test name. Default: `None`
- **argv** – Command line args. Default: `sys.argv`
- **testRunner** – *IGNORED*
- **testLoader** – *IGNORED*
- **exit** – Exit after running tests?
- **verbosity** – Base verbosity
- **failfast** – *IGNORED*
- **catchbreak** – *IGNORED*
- **buffer** – *IGNORED*
- **plugins** – List of additional plugin modules to load
- **excludePlugins** – List of plugin modules to exclude
- **extraHooks** – List of hook names and plugin *instances* to register with the session's hooks system. Each item in the list must be a 2-tuple of (hook name, plugin instance)

**sessionClass**

The class to instantiate to create a test run configuration session. Default: `nose2.session.Session`

**loaderClass**

The class to instantiate to create a test loader. Default: `nose2.loader.PluggableTestLoader`.

**Warning**

Overriding this attribute is the only way to customize the test loader class. Passing a test loader to `__init__()` does not work.

**runnerClass**

The class to instantiate to create a test runner. Default: `nose2.runner.PluggableTestRunner`.

**Warning**

Overriding this attribute is the only way to customize the test runner class. Passing a test runner to `__init__()` does not work.

**defaultPlugins**

List of default plugin modules to load.

**createTests()**

Create top-level test suite

**findConfigFiles(cfg\_args)**

Find available config files

**classmethod getCurrentSession()**

Returns the current session, or None if no `nose2.session.Session` is running.

**handleArgs(args)**

Handle further arguments.

Handle arguments parsed out of command line after plugins have been loaded (and injected their argument configuration).

**handleCfgArgs(cfg\_args)**

Handle initial arguments.

Handle the initial, pre-plugin arguments parsed out of the command line.

**loadPlugins()**

Load available plugins

`self.defaultPlugins`()` and `self.excludePlugins()` are passed to the session to alter the list of plugins that will be loaded.

This method also registers any (hook, plugin) pairs set in `self.hooks`. This is a good way to inject plugins that fall outside of the normal loading procedure, for example, plugins that need some runtime information that can't easily be passed to them through the configuration system.

**loaderClass**

alias of `PluggableTestLoader`

**parseArgs(argv)**

Parse command line args

Parses arguments and creates a configuration session, then calls `createTests()`.

**runTests()**

Run tests

**runnerClass**

alias of `PluggableTestRunner`

**sessionClass**

alias of `Session`

**setInitialArguments()**

Set pre-plugin command-line arguments.

This set of arguments is parsed out of the command line before plugins are loaded.

**nose2.main.discover(\*args, \*\*kwargs)**

Main entry point for test discovery.

Running discover calls *nose2.main.PluggableTestProgram*, passing through all arguments and keyword arguments **except module**: module is discarded, to force test discovery.

**nose2.main.main**

alias of *PluggableTestProgram*

## 9.2.2 nose2.exceptions

**exception nose2.exceptions.LoadTestsFailure**

Raised when a test cannot be loaded

**exception nose2.exceptions.TestNotFoundError**

Raised when a named test cannot be found

## 9.2.3 nose2.loader

**class nose2.loader.PluggableTestLoader(session)**

Test loader that defers all loading to plugins

**Parameters**

**session** – Test run session.

**suiteClass**

Suite class to use. Default: `unittest.TestSuite`.

**discover(start\_dir=None, pattern=None)**

Compatibility shim for load\_tests protocol.

**failedImport(name)**

Make test case representing a failed import.

**failedLoadTests(name, exception)**

Make test case representing a failed test load.

**loadTestsFromModule(module)**

Load tests from module.

Fires *loadTestsFromModule()* hook.

**loadTestsFromName(name, module=None)**

Load tests from test name.

Fires *loadTestsFromName()* hook.

**loadTestsFromNames(testNames, module=None)**

Load tests from test names.

Fires *loadTestsFromNames()* hook.

**sortTestMethodsUsing(name)**

Sort key for test case test methods.

**suiteClass**

alias of TestSuite

**9.2.4 nose2.result****class** nose2.result.PluggableTestResult(*session*)

Test result that defers to plugins.

All test outcome recording and reporting is deferred to plugins, which are expected to implement `startTest()`, `stopTest()`, `testOutcome()`, and `wasSuccessful()`.

**Parameters****session** – Test run session.**shouldStop**

When True, test run should stop before running another test.

**addError**(*test*, *err*)

Test case resulted in error.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addExpectedFailure**(*test*, *err*)

Test case resulted in expected failure.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addFailure**(*test*, *err*)

Test case resulted in failure.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addSkip**(*test*, *reason*)

Test case was skipped.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addSubTest**(*test*, *subtest*, *err*)

Called at the end of a subtest.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addSuccess**(*test*)

Test case resulted in success.

Fires `setTestOutcome()` and `testOutcome()` hooks.**addUnexpectedSuccess**(*test*)

Test case resulted in unexpected success.

Fires `setTestOutcome()` and `testOutcome()` hooks.**startTest**(*test*)

Start a test case.

Fires `startTest()` hook.**stop**()

Stop test run.

Fires `resultStop()` hook, and sets `self.shouldStop` to `event.shouldStop`.

**stopTest**(*test*)

Stop a test case.

Fires *stopTest()* hook.

**wasSuccessful**()

Was test run successful?

Fires *wasSuccessful()* hook, and returns `event.success`.

## 9.2.5 nose2.runner

**class** `nose2.runner.PluggableTestRunner`(*session*)

Test runner that defers most work to plugins.

**Parameters**

**session** – Test run session

**resultClass**

Class to instantiate to create test result. Default: *nose2.result.PluggableTestResult*.

**resultClass**

alias of *PluggableTestResult*

**run**(*test*)

Run tests.

**Parameters**

**test** – A unittest `TestSuite` or `TestClass`.

**Returns**

Test result

Fires *startTestRun()* and *stopTestRun()* hooks.

## 9.2.6 nose2.util

`nose2.util.call_with_args_if_expected`(*func*, \**args*)

Take `:func:` and call it with supplied `:args:`, in case that signature expects any. Otherwise call the function without any arguments.

`nose2.util.ensure_importable`(*dirname*)

Ensure a directory is on `sys.path`.

`nose2.util.exc_info_to_string`(*err*, *test*)

Format exception info for output

`nose2.util.format_traceback`(*test*, *err*)

Converts a `sys.exc_info()` -style tuple of values into a string.

`nose2.util.has_module_fixtures`(*test*)

Does this test live in a module with module fixtures?

`nose2.util.ispackage`(*path*)

Is this path a package directory?



`nose2.util.ln(label, char='-', width=70)`

Draw a divider, with `label` in the middle.

```
>>> ln('hello there')
'----- hello there -----'
```

`width` and divider `char` may be specified. Defaults are 70 and '-', respectively.

`nose2.util.module_from_name(name)`

Import module from `name`

`nose2.util.name_from_args(name, index, args)`

Create test name from test args

`nose2.util.name_from_path(path)`

Translate `path` into module name

Returns a two-element tuple:

1. a dotted module name that can be used in an import statement (e.g., `pkg1.test.test_things`)
2. a full path to filesystem directory, which must be on `sys.path` for the import to succeed.

`nose2.util.num_expected_args(func)`

Return the number of arguments that `:func:` expects

`nose2.util.object_from_name(name, module=None)`

Given a dotted name, return the corresponding object.

Getting the object can fail for two reason:

- the object is a module that cannot be imported.
- the object is a class or a function that does not exists.

Since we cannot distinguish between these two cases, we assume we are in the first one. We expect the stacktrace is explicit enough for the user to understand the error.

`nose2.util.parse_log_level(lvl)`

Return numeric log level given a string

`nose2.util.safe_decode(string)`

Safely decode a byte string into unicode

`nose2.util.test_from_name(name, module)`

Import test from `name`

`nose2.util.transplant_class(cls, module)`

Make `cls` appear to reside in `module`.

#### Parameters

- **cls** – A class
- **module** – A module name

#### Returns

A subclass of `cls` that appears to have been defined in `module`.

The returned class's `__name__` will be equal to `cls.__name__`, and its `__module__` equal to `module`.

`nose2.util.try_import_module_from_name(splitted_name)`

Try to find the longest importable from the `splitted_name`, and return the corresponding module, as well as the potential `ImportError` exception that occurs when trying to import a longer name.

For instance, if `splitted_name` is `['a', 'b', 'c']` but only `a.b` is importable, this function:

1. tries to import `a.b.c` and fails
2. tries to import `a.b` and succeeds
3. return `a.b` and the exception that occurred at step 1.

`nose2.util.valid_module_name(path)`

Is `path` a valid module name?

## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## PYTHON MODULE INDEX

### n

- [nose2.events](#), 90
- [nose2.exceptions](#), 114
- [nose2.loader](#), 114
- [nose2.main](#), 112
- [nose2.plugins.attrib](#), 46
- [nose2.plugins.buffer](#), 31
- [nose2.plugins.collect](#), 59
- [nose2.plugins.coverage](#), 35
- [nose2.plugins.debugger](#), 32
- [nose2.plugins.doctests](#), 57
- [nose2.plugins.dundertest](#), 30
- [nose2.plugins.failfast](#), 33
- [nose2.plugins.junitxml](#), 39
- [nose2.plugins.layers](#), 56
- [nose2.plugins.loader.discovery](#), 23
- [nose2.plugins.loader.eggdiscovery](#), 66
- [nose2.plugins.loader.functions](#), 23
- [nose2.plugins.loader.generators](#), 25
- [nose2.plugins.loader.loadtests](#), 29
- [nose2.plugins.loader.parameters](#), 25
- [nose2.plugins.loader.testcases](#), 27
- [nose2.plugins.loader.testclasses](#), 27
- [nose2.plugins.logcapture](#), 34
- [nose2.plugins.mp](#), 51
- [nose2.plugins.outcomes](#), 58
- [nose2.plugins.prettyassert](#), 38
- [nose2.plugins.printheooks](#), 63
- [nose2.plugins.prof](#), 62
- [nose2.plugins.result](#), 30
- [nose2.plugins.testid](#), 60
- [nose2.result](#), 115
- [nose2.runner](#), 116
- [nose2.tools.such](#), 74
- [nose2.util](#), 116



## Symbols

- A
  - command line option, 46
- B
  - command line option, 32
- C
  - command line option, 37
- D
  - command line option, 33
- E
  - command line option, 46
- F
  - command line option, 33
- I
  - command line option, 61
- N
  - command line option, 52
- P
  - command line option, 63, 64
- X
  - command line option, 41
- attribute
  - command line option, 46
- collect-only
  - command line option, 60
- config
  - command line option, 18
- coverage
  - command line option, 37
- coverage-config
  - command line option, 37
- coverage-report
  - command line option, 37
- debugger
  - command line option, 33
- eval-attribute
  - command line option, 46
- fail-fast
  - command line option, 33
- junit-xml
  - command line option, 41
- junit-xml-path
  - command line option, 41

- command line option, 41
- layer-reporter
  - command line option, 57
- log-capture
  - command line option, 35
- no-plugins
  - command line option, 19
- no-user-config
  - command line option, 18
- output-buffer
  - command line option, 32
- pretty-assert
  - command line option, 38
- print-hooks
  - command line option, 64
- processes
  - command line option, 52
- profile
  - command line option, 63
- project-directory
  - command line option, 16
- set-outcomes
  - command line option, 59
- start-dir
  - command line option, 16
- top-level-directory
  - command line option, 16
- with-coverage
  - command line option, 37
- with-doctest
  - command line option, 58
- with-id
  - command line option, 61
- c
  - command line option, 18
- s
  - command line option, 16
- t
  - command line option, 16

## A

AC) (in module *nose2.tools.such*), 74

`addArgument()` (*nose2.events.Plugin method*), 108  
`addAssertDetail()` (*nose2.plugins.prettyassert.PrettyAssert static method*), 38  
`addError()` (*nose2.result.PluggableTestResult method*), 115  
`addExpectedFailure()` (*nose2.result.PluggableTestResult method*), 115  
`addFailure()` (*nose2.result.PluggableTestResult method*), 115  
`addFlag()` (*nose2.events.Plugin method*), 108  
`addMethod()` (*nose2.events.PluginInterface method*), 109  
`addMethods()` (*nose2.events.Plugin method*), 108  
`addOption()` (*nose2.events.Plugin method*), 108  
`addSkip()` (*nose2.result.PluggableTestResult method*), 115  
`addSubTest()` (*nose2.result.PluggableTestResult method*), 115  
`addSuccess()` (*nose2.result.PluggableTestResult method*), 115  
`addUnexpectedSuccess()` (*nose2.result.PluggableTestResult method*), 115  
`afterInteraction()`  
    built-in function, 104  
`afterInteraction()` (*nose2.plugins.buffer.OutputBufferPlugin method*), 32  
`afterSummaryReport()`  
    built-in function, 104  
`afterSummaryReport()` (*nose2.plugins.coverage.Coverage method*), 37  
`afterTestRun()`  
    built-in function, 103  
`afterTestRun()` (*nose2.plugins.result.ResultReporter method*), 31  
`always-on`  
    configvar, 23–31, 33, 34, 36, 38, 41, 51, 56–58, 60–63, 67  
`alwaysOn` (*nose2.events.Plugin attribute*), 108  
`argparse` (*nose2.session.Session attribute*), 105  
`args` (*nose2.events.CommandLineArgsEvent attribute*), 90  
`as_bool()` (*nose2.config.Config method*), 107  
`as_float()` (*nose2.config.Config method*), 107  
`as_int()` (*nose2.config.Config method*), 107  
`as_list()` (*nose2.config.Config method*), 107  
`as_str()` (*nose2.config.Config method*), 107  
`AttributeSelector` (class in *nose2.plugins.attrib*), 46

**B**

`beforeErrorList()`  
    built-in function, 103  
`beforeInteraction()`  
    built-in function, 104  
`beforeInteraction()` (*nose2.plugins.buffer.OutputBufferPlugin method*), 32  
`beforeSummaryReport()`  
    built-in function, 104  
`beforeSummaryReport()` (*nose2.plugins.coverage.Coverage method*), 37  
`beforeSummaryReport()` (*nose2.plugins.prof.Profiler method*), 63  
`bind_address`  
    configvar, 51  
built-in function  
    `afterInteraction()`, 104  
    `afterSummaryReport()`, 104  
    `afterTestRun()`, 103  
    `beforeErrorList()`, 103  
    `beforeInteraction()`, 104  
    `beforeSummaryReport()`, 104  
    `createTests()`, 99  
    `describeTest()`, 101  
    `getTestCaseNames()`, 100  
    `handleArgs()`, 98  
    `handleFile()`, 99  
    `loadTestsFromModule()`, 99  
    `loadTestsFromName()`, 99  
    `loadTestsFromNames()`, 99  
    `loadTestsFromTestCase()`, 99  
    `matchPath()`, 99  
    `outcomeDetail()`, 104  
    `pluginsLoaded()`, 98  
    `registerInSubprocess()`, 48  
    `reportError()`, 101  
    `reportExpectedFailure()`, 102  
    `reportFailure()`, 102  
    `reportOtherOutcome()`, 102  
    `reportSkip()`, 102  
    `reportStartTest()`, 101  
    `reportSuccess()`, 101  
    `reportUnexpectedSuccess()`, 102  
    `resultCreated()`, 100  
    `resultStop()`, 103  
    `runnerCreated()`, 100  
    `setTestOutcome()`, 101  
    `startLayerSetup()`, 100  
    `startLayerSetupTest()`, 100  
    `startLayerTeardown()`, 103  
    `startLayerTeardownTest()`, 102  
    `startSubprocess()`, 49  
    `startTest()`, 101  
    `startTestRun()`, 100  
    `stopLayerSetup()`, 100  
    `stopLayerSetupTest()`, 101  
    `stopLayerTeardown()`, 103



stopLayerTeardownTest(), 103  
 stopSubprocess(), 49  
 stopTest(), 102  
 stopTestRun(), 103  
 testOutcome(), 101  
 wasSuccessful(), 104

## C

call\_with\_args\_if\_expected() (in module  
     nose2.util), 116  
 clear-handlers  
     configvar, 34  
 code-directories  
     configvar, 18  
 CollectOnly (class in nose2.plugins.collect), 60  
 collectTests() (nose2.plugins.collect.CollectOnly  
     method), 60  
 colors  
     configvar, 56  
 command line option  
     -A, 46  
     -B, 32  
     -C, 37  
     -D, 33  
     -E, 46  
     -F, 33  
     -I, 61  
     -N, 52  
     -P, 63, 64  
     -X, 41  
     --attribute, 46  
     --collect-only, 60  
     --config, 18  
     --coverage, 37  
     --coverage-config, 37  
     --coverage-report, 37  
     --debugger, 33  
     --eval-attribute, 46  
     --fail-fast, 33  
     --junit-xml, 41  
     --junit-xml-path, 41  
     --layer-reporter, 57  
     --log-capture, 35  
     --no-plugins, 19  
     --no-user-config, 18  
     --output-buffer, 32  
     --pretty-assert, 38  
     --print-hooks, 64  
     --processes, 52  
     --profile, 63  
     --project-directory, 16  
     --set-outcomes, 59  
     --start-dir, 16  
     --top-level-directory, 16

--with-coverage, 37  
 --with-doctest, 58  
 --with-id, 61  
 -c, 18  
 -s, 16  
 -t, 16

CommandLineArgsEvent (class in nose2.events), 90  
 commandLineSwitch (nose2.events.Plugin attribute),  
     107  
 Config (class in nose2.config), 107  
 config (nose2.events.Plugin attribute), 107  
 configClass (nose2.session.Session attribute), 105  
 configSection (nose2.events.Plugin attribute), 108  
 configvar  
     always-on, 23–31, 33, 34, 36, 38, 41, 51, 56–58,  
         60–63, 67  
     bind\_address, 51  
     clear-handlers, 34  
     code-directories, 18  
     colors, 56  
     coverage, 36  
     coverage-combine, 36  
     coverage-config, 36  
     coverage-report, 36  
     date-format, 34  
     descriptions, 30  
     errors-only, 33  
     exclude-plugins, 19  
     extensions, 57  
     filename, 62  
     filter, 34  
     format, 34  
     highlight-words, 56  
     id-file, 61  
     indent, 56  
     keep\_restricted, 41  
     log-level, 34  
     path, 41  
     plugins, 19  
     processes, 51  
     restrict, 62  
     sort, 62  
     start-dir, 18  
     stderr, 31  
     stdout, 32  
     test\_fullname, 41  
     test\_properties, 41  
     test-file-pattern, 18  
     test-method-prefix, 18  
     test-run-timeout, 51  
     treat-as-fail, 59  
     treat-as-skip, 59  
 connection (nose2.plugins.mp.SubprocessEvent at-  
     tribute), 49

coverage  
    configvar, 36  
Coverage (class in nose2.plugins.coverage), 37  
coverage-combine  
    configvar, 36  
coverage-config  
    configvar, 36  
coverage-report  
    configvar, 36  
CreatedTestSuiteEvent (class in nose2.events), 90  
createTests()  
    built-in function, 99  
createTests() (nose2.main.PluggableTestProgram  
    method), 113  
createTests() (nose2.plugins.coverage.Coverage  
    method), 37  
createTests() (nose2.tools.such.Scenario method), 74  
CreateTestsEvent (class in nose2.events), 90

## D

date-format  
    configvar, 34  
Debugger (class in nose2.plugins.debugger), 33  
defaultPlugins (nose2.main.PluggableTestProgram  
    attribute), 113  
describeTest()  
    built-in function, 101  
DescribeTestEvent (class in nose2.events), 91  
description (nose2.events.DescribeTestEvent  
    attribute), 91  
descriptions  
    configvar, 30  
discover() (in module nose2.main), 114  
discover() (nose2.loader.PluggableTestLoader  
    method), 114  
DiscoveryLoader (class in  
    nose2.plugins.loader.discovery), 23  
DocTestLoader (class in nose2.plugins.doctests), 58  
DunderTestFilter (class in nose2.plugins.dundertest),  
    30

## E

EggDiscoveryLoader (class in  
    nose2.plugins.loader.eggdiscovery), 67  
ensure\_importable() (in module nose2.util), 116  
errorList (nose2.events.DescribeTestEvent  
    attribute), 91  
errors-only  
    configvar, 33  
Event (class in nose2.events), 91  
exc\_info (nose2.events.TestOutcomeEvent  
    attribute), 97  
exc\_info\_to\_string() (in module nose2.util), 116  
exclude-plugins  
    configvar, 19

excludedNames (nose2.events.GetTestCaseNamesEvent  
    attribute), 91  
executeTests (nose2.events.StartTestRunEvent  
    attribute), 96  
executeTests (nose2.plugins.mp.SubprocessEvent  
    attribute), 49  
expected (nose2.events.TestOutcomeEvent  
    attribute), 97  
extensions  
    configvar, 57  
extraDetail (nose2.events.OutcomeDetailEvent  
    attribute), 94  
extraNames (nose2.events.GetTestCaseNamesEvent  
    attribute), 91  
extraTests (nose2.events.HandleFileEvent  
    attribute), 92  
extraTests (nose2.events.LoadFromModuleEvent  
    attribute), 92  
extraTests (nose2.events.LoadFromNameEvent  
    attribute), 92  
extraTests (nose2.events.LoadFromNamesEvent  
    attribute), 93  
extraTests (nose2.events.LoadFromTestCaseEvent  
    attribute), 93

## F

failedImport() (nose2.loader.PluggableTestLoader  
    method), 114  
failedLoadTests() (nose2.loader.PluggableTestLoader  
    method), 114  
FailFast (class in nose2.plugins.failfast), 34  
filename  
    configvar, 62  
filter  
    configvar, 34  
findConfigFiles() (nose2.main.PluggableTestProgram  
    method), 113  
format  
    configvar, 34  
format\_traceback() (in module nose2.util), 116  
Functions (class in nose2.plugins.loader.functions), 24

## G

Generators (class in nose2.plugins.loader.generators),  
    25  
get() (nose2.config.Config method), 107  
get() (nose2.session.Session method), 105  
getCurrentSession()  
    (nose2.main.PluggableTestProgram  
    class  
    method), 113  
getTestCaseNames()  
    built-in function, 100  
getTestCaseNames() (nose2.plugins.loader.generators.Generators  
    method), 25

- getTestCaseNames() (*nose2.plugins.loader.parameters.Parameters* method), 26
- GetTestCaseNamesEvent (*class in nose2.events*), 91
- getTestMethodNames() (*in module nose2.plugins.loader.testclasses*), 28
- ## H
- handleArgs() built-in function, 98
- handleArgs() (*nose2.main.PluggableTestProgram* method), 113
- handleArgs() (*nose2.plugins.attrib.AttributeSelector* method), 46
- handleArgs() (*nose2.plugins.coverage.Coverage* method), 37
- handleArgs() (*nose2.plugins.junitxml.JUnitXmlReporter* method), 42
- handleCfgArgs() (*nose2.main.PluggableTestProgram* method), 113
- handled (*nose2.events.Event* attribute), 91
- handleDir() (*nose2.plugins.loader.loadtests.LoadTestsLoader* method), 29
- handleFile() built-in function, 99
- handleFile() (*nose2.plugins.doctests.DocTestLoader* method), 58
- HandleFileEvent (*class in nose2.events*), 91
- has\_module\_fixtures() (*in module nose2.util*), 116
- has\_setup() (*nose2.tools.such.Scenario* method), 74
- has\_teardown() (*nose2.tools.such.Scenario* method), 74
- has\_test\_setup() (*nose2.tools.such.Scenario* method), 74
- has\_test\_teardown() (*nose2.tools.such.Scenario* method), 75
- having() (*nose2.tools.such.Scenario* method), 75
- highlight-words configvar, 56
- Hook (*class in nose2.events*), 109
- hookClass (*nose2.events.PluginInterface* attribute), 109
- hooks (*nose2.session.Session* attribute), 105
- ## I
- id-file configvar, 61
- indent configvar, 56
- ispackage() (*in module nose2.util*), 116
- isPluginLoaded() (*nose2.session.Session* method), 106
- isTestMethod (*nose2.events.GetTestCaseNamesEvent* attribute), 91
- JUnitXmlReporter (*class in nose2.plugins.junitxml*), 42
- ## K
- keep\_restricted configvar, 41
- ## L
- Layer (*built-in class*), 53
- layer (*nose2.events.StartLayerSetupEvent* attribute), 95
- layer (*nose2.events.StartLayerSetupTestEvent* attribute), 95
- layer (*nose2.events.StartLayerTeardownEvent* attribute), 95
- layer (*nose2.events.StartLayerTeardownTestEvent* attribute), 95
- layer (*nose2.events.StopLayerSetupEvent* attribute), 96
- layer (*nose2.events.StopLayerSetupTestEvent* attribute), 96
- layer (*nose2.events.StopLayerTeardownEvent* attribute), 96
- layer (*nose2.events.StopLayerTeardownTestEvent* attribute), 96
- LayerReporter (*class in nose2.plugins.layers*), 57
- Layers (*class in nose2.plugins.layers*), 57
- libDirs (*nose2.session.Session* attribute), 105
- ln() (*in module nose2.util*), 116
- loadConfigFiles() (*nose2.session.Session* method), 106
- loader (*nose2.events.CreateTestsEvent* attribute), 90
- loader (*nose2.events.GetTestCaseNamesEvent* attribute), 91
- loader (*nose2.events.HandleFileEvent* attribute), 92
- loader (*nose2.events.LoadFromModuleEvent* attribute), 92
- loader (*nose2.events.LoadFromNameEvent* attribute), 92
- loader (*nose2.events.LoadFromNamesEvent* attribute), 93
- loader (*nose2.events.LoadFromTestCaseEvent* attribute), 93
- loader (*nose2.plugins.mp.SubprocessEvent* attribute), 49
- loaderClass (*nose2.main.PluggableTestProgram* attribute), 112, 113
- LoadFromModuleEvent (*class in nose2.events*), 92
- LoadFromNameEvent (*class in nose2.events*), 92
- LoadFromNamesEvent (*class in nose2.events*), 93
- LoadFromTestCaseEvent (*class in nose2.events*), 93
- loadIds() (*nose2.plugins.testid.TestId* method), 61
- loadPlugins() (*nose2.main.PluggableTestProgram* method), 113
- loadPlugins() (*nose2.session.Session* method), 106

loadPluginsFromModule() (*nose2.session.Session* method), 106

LoadTestsFailure, 114

loadTestsFromModule() built-in function, 99

loadTestsFromModule() (*nose2.loader.PluggableTestLoader* method), 114

loadTestsFromModule() (*nose2.plugins.loader.functions.Functions* method), 24

loadTestsFromModule() (*nose2.plugins.loader.generators.Generators* method), 25

loadTestsFromModule() (*nose2.plugins.loader.parameters.Parameters* method), 26

loadTestsFromModule() (*nose2.plugins.loader.testcases.TestCaseLoader* method), 27

loadTestsFromModule() (*nose2.plugins.loader.testclasses.TestClassLoader* method), 28

loadTestsFromName() built-in function, 99

loadTestsFromName() (*nose2.loader.PluggableTestLoader* method), 114

loadTestsFromName() (*nose2.plugins.loader.discovery.DiscoveryLoader* method), 23

loadTestsFromName() (*nose2.plugins.loader.eggdiscovery.EggDiscoveryLoader* method), 67

loadTestsFromName() (*nose2.plugins.loader.functions.Functions* method), 24

loadTestsFromName() (*nose2.plugins.loader.generators.Generators* method), 25

loadTestsFromName() (*nose2.plugins.loader.parameters.Parameters* method), 26

loadTestsFromName() (*nose2.plugins.loader.testcases.TestCaseLoader* method), 27

loadTestsFromName() (*nose2.plugins.loader.testclasses.TestClassLoader* method), 29

loadTestsFromName() (*nose2.plugins.testid.TestId* method), 61

loadTestsFromNames() built-in function, 99

loadTestsFromNames() (*nose2.loader.PluggableTestLoader* method), 114

loadTestsFromNames() (*nose2.plugins.loader.discovery.DiscoveryLoader* method), 23

loadTestsFromNames() (*nose2.plugins.loader.eggdiscovery.EggDiscoveryLoader* method), 67

loadTestsFromNames() (*nose2.plugins.testid.TestId* method), 61

loadTestsFromTestCase() built-in function, 99

loadTestsFromTestCase() (*nose2.plugins.loader.generators.Generators* method), 25

loadTestsFromTestClass() (in *nose2.plugins.loader.testclasses*), 27

LoadTestsLoader (class in *nose2.plugins.loader.loadtests*), 29

log-level configvar, 34

LogCapture (class in *nose2.plugins.logcapture*), 35

longLabel (*nose2.events.TestOutcomeEvent* attribute), 97

## M

main (in module *nose2.main*), 114

matchPath() built-in function, 99

MatchPathEvent (class in *nose2.events*), 93

metadata (*nose2.events.Event* attribute), 91

method (*nose2.events.Hook* attribute), 109

methods (*nose2.events.PluginInterface* attribute), 109

module

- nose2.events*, 90
- nose2.exceptions*, 114
- nose2.loader*, 114
- nose2.main*, 112
- nose2.plugins.attrib*, 46
- nose2.plugins.buffer*, 31
- nose2.plugins.collect*, 59
- nose2.plugins.coverage*, 35
- nose2.plugins.debugger*, 32
- nose2.plugins.doctests*, 57
- nose2.plugins.dundertest*, 30
- nose2.plugins.failfast*, 33
- nose2.plugins.junitxml*, 39
- nose2.plugins.layers*, 56
- nose2.plugins.loader.discovery*, 23
- nose2.plugins.loader.eggdiscovery*, 66
- nose2.plugins.loader.functions*, 23
- nose2.plugins.loader.generators*, 25
- nose2.plugins.loader.loadtests*, 29
- nose2.plugins.loader.parameters*, 25

nose2.plugins.loader.testcases, 27  
 nose2.plugins.loader.testclasses, 27  
 nose2.plugins.logcapture, 34  
 nose2.plugins.mp, 51  
 nose2.plugins.outcomes, 58  
 nose2.plugins.prettyassert, 38  
 nose2.plugins.printheooks, 63  
 nose2.plugins.prof, 62  
 nose2.plugins.result, 30  
 nose2.plugins.testid, 60  
 nose2.result, 115  
 nose2.runner, 116  
 nose2.tools.such, 74  
 nose2.util, 116  
 module (*nose2.events.CreateTestsEvent* attribute), 90  
 module (*nose2.events.LoadFromModuleEvent* attribute), 92  
 module (*nose2.events.LoadFromNameEvent* attribute), 92  
 module (*nose2.events.LoadFromNamesEvent* attribute), 93  
 module\_from\_name() (in module *nose2.util*), 117  
 moduleLoadedSuite()  
     (*nose2.plugins.attrib.AttributeSelector* method), 47  
 moduleLoadedSuite()  
     (*nose2.plugins.loader.loadtests.LoadTestsLoader* method), 29  
 ModuleSuiteEvent (class in *nose2.events*), 93  
 MultiProcess (class in *nose2.plugins.mp*), 52  
  
**N**  
 name (*nose2.events.HandleFileEvent* attribute), 92  
 name (*nose2.events.LoadFromNameEvent* attribute), 92  
 name (*nose2.events.MatchPathEvent* attribute), 93  
 name\_from\_args() (in module *nose2.util*), 117  
 name\_from\_path() (in module *nose2.util*), 117  
 names (*nose2.events.CreateTestsEvent* attribute), 90  
 names (*nose2.events.LoadFromNamesEvent* attribute), 93  
 nextId() (*nose2.plugins.testid.TestId* method), 61  
 nose2.events  
     module, 90  
 nose2.exceptions  
     module, 114  
 nose2.loader  
     module, 114  
 nose2.main  
     module, 112  
 nose2.plugins.attrib  
     module, 46  
 nose2.plugins.buffer  
     module, 31  
 nose2.plugins.collect  
     module, 59  
 nose2.plugins.coverage  
     module, 35  
 nose2.plugins.debugger  
     module, 32  
 nose2.plugins.doctests  
     module, 57  
 nose2.plugins.dundertest  
     module, 30  
 nose2.plugins.failfast  
     module, 33  
 nose2.plugins.junitxml  
     module, 39  
 nose2.plugins.layers  
     module, 56  
 nose2.plugins.loader.discovery  
     module, 23  
 nose2.plugins.loader.eggdiscovery  
     module, 66  
 nose2.plugins.loader.functions  
     module, 23  
 nose2.plugins.loader.generators  
     module, 25  
 nose2.plugins.loader.loadtests  
     module, 29  
 nose2.plugins.loader.parameters  
     module, 25  
 nose2.plugins.loader.testcases  
     module, 27  
 nose2.plugins.loader.testclasses  
     module, 27  
 nose2.plugins.logcapture  
     module, 34  
 nose2.plugins.mp  
     module, 51  
 nose2.plugins.outcomes  
     module, 58  
 nose2.plugins.prettyassert  
     module, 38  
 nose2.plugins.printheooks  
     module, 63  
 nose2.plugins.prof  
     module, 62  
 nose2.plugins.result  
     module, 30  
 nose2.plugins.testid  
     module, 60  
 nose2.result  
     module, 115  
 nose2.runner  
     module, 116  
 nose2.tools.such  
     module, 74  
 nose2.util  
     module, 116



num\_expected\_args() (in module nose2.util), 117

## O

object\_from\_name() (in module nose2.util), 117

outcome (nose2.events.TestOutcomeEvent attribute), 97

outcomeDetail()

built-in function, 104

outcomeDetail() (nose2.plugins.buffer.OutputBufferPlugin method), 32

outcomeDetail() (nose2.plugins.logcapture.LogCapture method), 35

OutcomeDetailEvent (class in nose2.events), 93

outcomeEvent (nose2.events.OutcomeDetailEvent attribute), 94

Outcomes (class in nose2.plugins.outcomes), 59

OutputBufferPlugin (class in nose2.plugins.buffer), 32

## P

Parameters (class in nose2.plugins.loader.parameters), 26

params() (in module nose2.tools), 68

parse\_log\_level() (in module nose2.util), 117

parseArgs() (nose2.main.PluggableTestProgram method), 113

path

configvar, 41

path (nose2.events.HandleFileEvent attribute), 92

path (nose2.events.MatchPathEvent attribute), 93

pattern (nose2.events.HandleFileEvent attribute), 92

pattern (nose2.events.MatchPathEvent attribute), 93

pdb (nose2.plugins.debugger.Debugger attribute), 33

PluggableTestLoader (class in nose2.loader), 114

PluggableTestProgram (class in nose2.main), 112

PluggableTestResult (class in nose2.result), 115

PluggableTestRunner (class in nose2.runner), 116

Plugin (class in nose2.events), 107

pluginargs (nose2.session.Session attribute), 105

pluginClasses (nose2.plugins.mp.RegisterInSubprocessEvent attribute), 49

PluginInterface (class in nose2.events), 109

plugins

configvar, 19

plugins (nose2.events.Hook attribute), 109

plugins (nose2.plugins.mp.SubprocessEvent attribute), 49

plugins (nose2.session.Session attribute), 105

pluginsLoaded (nose2.events.PluginsLoadedEvent attribute), 94

pluginsLoaded()

built-in function, 98

PluginsLoadedEvent (class in nose2.events), 94

prepareSysPath() (nose2.session.Session method), 106

preRegistrationMethods

(nose2.events.PluginInterface attribute), 109

PrettyAssert (class in nose2.plugins.prettyassert), 38

PrintHooks (class in nose2.plugins.printheooks), 64

processes

configvar, 51

procs (nose2.plugins.mp.MultiProcess property), 52

Profiler (class in nose2.plugins.prof), 63

## R

reason (nose2.events.TestOutcomeEvent attribute), 97

register() (nose2.events.Plugin method), 109

register() (nose2.events.PluginInterface method), 109

register() (nose2.plugins.loader.testclasses.TestClassLoader method), 29

register() (nose2.plugins.printheooks.PrintHooks method), 64

registerInSubprocess()

built-in function, 48

RegisterInSubprocessEvent (class in nose2.plugins.mp), 49

registerPlugin() (nose2.session.Session method), 106

reportCategories (nose2.events.ReportSummaryEvent attribute), 94

reportError()

built-in function, 101

reportExpectedFailure()

built-in function, 102

reportFailure()

built-in function, 102

reportOtherOutcome()

built-in function, 102

reportSkip()

built-in function, 102

reportStartTest()

built-in function, 101

reportStartTest() (nose2.plugins.testid.TestId method), 61

reportSuccess()

built-in function, 101

ReportSummaryEvent (class in nose2.events), 94

ReportTestEvent (class in nose2.events), 94

reportUnexpectedSuccess()

built-in function, 102

restrict

configvar, 62

result (nose2.events.ResultCreatedEvent attribute), 94

result (nose2.events.ResultStopEvent attribute), 94

result (nose2.events.ResultSuccessEvent attribute), 95

result (nose2.events.StartTestEvent attribute), 95

result (nose2.events.StartTestRunEvent attribute), 96

result (nose2.events.StopTestEvent attribute), 97

result (*nose2.events.StopTestRunEvent* attribute), 97  
 result (*nose2.events.TestOutcomeEvent* attribute), 97  
 result (*nose2.plugins.mp.SubprocessEvent* attribute), 49  
 resultClass (*nose2.runner.PluggableTestRunner* attribute), 116  
 resultCreated()  
     built-in function, 100  
 resultCreated() (*nose2.plugins.failfast.FailFast* method), 34  
 ResultCreatedEvent (class in *nose2.events*), 94  
 ResultReporter (class in *nose2.plugins.result*), 31  
 resultStop()  
     built-in function, 103  
 ResultStopEvent (class in *nose2.events*), 94  
 ResultSuccessEvent (class in *nose2.events*), 94  
 run() (*nose2.runner.PluggableTestRunner* method), 116  
 runner (*nose2.events.RunnerCreatedEvent* attribute), 95  
 runner (*nose2.events.StartTestRunEvent* attribute), 96  
 runner (*nose2.events.StopTestRunEvent* attribute), 97  
 runnerClass (*nose2.main.PluggableTestProgram* attribute), 112, 113  
 runnerCreated()  
     built-in function, 100  
 RunnerCreatedEvent (class in *nose2.events*), 95  
 runTests() (*nose2.main.PluggableTestProgram* method), 113

## S

safe\_decode() (in module *nose2.util*), 117  
 Scenario (class in *nose2.tools.such*), 74  
 Session (class in *nose2.session*), 105  
 session (*nose2.events.Plugin* attribute), 107  
 sessionClass (*nose2.main.PluggableTestProgram* attribute), 112, 113  
 setInitialArguments()  
     (*nose2.main.PluggableTestProgram* method), 113  
 setStartDir() (*nose2.session.Session* method), 106  
 setTestOutcome()  
     built-in function, 101  
 setTestOutcome() (*nose2.plugins.buffer.OutputBufferPlugin* method), 32  
 setTestOutcome() (*nose2.plugins.logcapture.LogCapture* method), 35  
 setTestOutcome() (*nose2.plugins.outcomes.Outcomes* method), 59  
 setUp() (Layer class method), 53  
 setVerbosity() (*nose2.session.Session* method), 106  
 shortLabel (*nose2.events.TestOutcomeEvent* attribute), 97  
 should() (*nose2.tools.such.Scenario* method), 75  
 shouldStop (*nose2.events.ResultStopEvent* attribute), 94  
 shouldStop (*nose2.result.PluggableTestResult* attribute), 115  
 sort  
     configvar, 62  
 sortTestMethodsUsing()  
     (*nose2.loader.PluggableTestLoader* method), 114  
 start-dir  
     configvar, 18  
 startDir (*nose2.session.Session* attribute), 105  
 startLayerSetup()  
     built-in function, 100  
 StartLayerSetupEvent (class in *nose2.events*), 95  
 startLayerSetupTest()  
     built-in function, 100  
 StartLayerSetupTestEvent (class in *nose2.events*), 95  
 startLayerTeardown()  
     built-in function, 103  
 StartLayerTeardownEvent (class in *nose2.events*), 95  
 startLayerTeardownTest()  
     built-in function, 102  
 StartLayerTeardownTestEvent (class in *nose2.events*), 95  
 startSubprocess()  
     built-in function, 49  
 startTest()  
     built-in function, 101  
 startTest() (*nose2.plugins.buffer.OutputBufferPlugin* method), 32  
 startTest() (*nose2.plugins.junitxml.JUnitXmlReporter* method), 42  
 startTest() (*nose2.plugins.logcapture.LogCapture* method), 35  
 startTest() (*nose2.plugins.result.ResultReporter* method), 31  
 startTest() (*nose2.result.PluggableTestResult* method), 115  
 StartTestEvent (class in *nose2.events*), 95  
 startTestRun()  
     built-in function, 100  
 startTestRun() (*nose2.plugins.collect.CollectOnly* method), 60  
 startTestRun() (*nose2.plugins.dundertest.DunderTestFilter* method), 30  
 startTestRun() (*nose2.plugins.logcapture.LogCapture* method), 35  
 startTestRun() (*nose2.plugins.prof.Profiler* method), 63  
 StartTestRunEvent (class in *nose2.events*), 96  
 startTime (*nose2.events.StartTestEvent* attribute), 95  
 startTime (*nose2.events.StartTestRunEvent* attribute), 96  
 stderr

configvar, 31  
 stdout  
   configvar, 32  
 stop() (*nose2.result.PluggableTestResult* method), 115  
 stopLayerSetup()  
   built-in function, 100  
 StopLayerSetupEvent (*class* in *nose2.events*), 96  
 stopLayerSetupTest()  
   built-in function, 101  
 StopLayerSetupTestEvent (*class* in *nose2.events*), 96  
 stopLayerTeardown()  
   built-in function, 103  
 StopLayerTeardownEvent (*class* in *nose2.events*), 96  
 stopLayerTeardownTest()  
   built-in function, 103  
 StopLayerTeardownTestEvent (*class* in *nose2.events*), 96  
 stopSubprocess()  
   built-in function, 49  
 stopTest()  
   built-in function, 102  
 stopTest() (*nose2.plugins.buffer.OutputBufferPlugin* method), 32  
 stopTest() (*nose2.plugins.logcapture.LogCapture* method), 35  
 stopTest() (*nose2.result.PluggableTestResult* method), 115  
 StopTestEvent (*class* in *nose2.events*), 97  
 stopTestEvent (*nose2.events.ReportSummaryEvent* attribute), 94  
 stopTestRun()  
   built-in function, 103  
 stopTestRun() (*nose2.plugins.junitxml.JUnitXmlReporter* method), 42  
 stopTestRun() (*nose2.plugins.testid.TestId* method), 61  
 StopTestRunEvent (*class* in *nose2.events*), 97  
 stopTime (*nose2.events.StopTestEvent* attribute), 97  
 stopTime (*nose2.events.StopTestRunEvent* attribute), 97  
 stream (*nose2.events.ReportSummaryEvent* attribute), 94  
 stream (*nose2.events.ReportTestEvent* attribute), 94  
 SubprocessEvent (*class* in *nose2.plugins.mp*), 49  
 success (*nose2.events.ResultSuccessEvent* attribute), 95  
 suite (*nose2.events.CreatedTestSuiteEvent* attribute), 90  
 suite (*nose2.events.StartTestRunEvent* attribute), 96  
 suiteClass (*nose2.loader.PluggableTestLoader* attribute), 114

**T**

tearDown() (*Layer* class method), 53  
 test (*nose2.events.DescribeTestEvent* attribute), 91  
 test (*nose2.events.StartLayerSetupTestEvent* attribute), 95  
 test (*nose2.events.StartLayerTeardownTestEvent* attribute), 95  
 test (*nose2.events.StartTestEvent* attribute), 95  
 test (*nose2.events.StopLayerSetupTestEvent* attribute), 96  
 test (*nose2.events.StopLayerTeardownTestEvent* attribute), 96  
 test (*nose2.events.StopTestEvent* attribute), 97  
 test (*nose2.events.TestOutcomeEvent* attribute), 97  
 test\_from\_name() (*in* module *nose2.util*), 117  
 test\_fullname  
   configvar, 41  
 test\_properties  
   configvar, 41  
 test-file-pattern  
   configvar, 18  
 test-method-prefix  
   configvar, 18  
 test-run-timeout  
   configvar, 51  
 testCase (*nose2.events.GetTestCaseNamesEvent* attribute), 91  
 testCase (*nose2.events.LoadFromTestCaseEvent* attribute), 93  
 TestCaseLoader (*class* in *nose2.plugins.loader.testcases*), 27  
 TestClassLoader (*class* in *nose2.plugins.loader.testclasses*), 28  
 testEvent (*nose2.events.ReportTestEvent* attribute), 94  
 testFilePattern (*nose2.session.Session* attribute), 105  
 TestId (*class* in *nose2.plugins.testid*), 61  
 testMethodPrefix (*nose2.events.GetTestCaseNamesEvent* attribute), 91  
 testMethodPrefix (*nose2.session.Session* attribute), 105  
 TestNotFoundError, 114  
 testOutcome()  
   built-in function, 101  
 testOutcome() (*nose2.plugins.debugger.Debugger* method), 33  
 testOutcome() (*nose2.plugins.failfast.FailFast* method), 34  
 testOutcome() (*nose2.plugins.junitxml.JUnitXmlReporter* method), 42  
 testOutcome() (*nose2.plugins.result.ResultReporter* method), 31  
 TestOutcomeEvent (*class* in *nose2.events*), 97  
 testSetUp() (*Layer* class method), 53  
 testTearDown() (*Layer* class method), 54  
 timeTaken (*nose2.events.StopTestRunEvent* attribute), 97  
 topLevelDir (*nose2.session.Session* attribute), 105  
 topLevelDirectory (*nose2.events.HandleFileEvent* attribute), 92



`transplant_class()` (in module *nose2.util*), 117  
`treat-as-fail`  
    `configvar`, 59  
`treat-as-skip`  
    `configvar`, 59  
`try_import_module_from_name()` (in module  
    *nose2.util*), 117

## U

`unittest` (*nose2.session.Session* attribute), 105  
`UserInteractionEvent` (class in *nose2.events*), 98

## V

`valid_module_name()` (in module *nose2.util*), 118  
`verbosity` (*nose2.session.Session* attribute), 105  
`version` (*nose2.events.Event* attribute), 91

## W

`wasSuccessful()`  
    built-in function, 104  
`wasSuccessful()` (*nose2.plugins.coverage.Coverage*  
    *method*), 37  
`wasSuccessful()` (*nose2.result.PluggableTestResult*  
    *method*), 116  
`with_setup()` (in module *nose2.tools.decorators*), 67  
`with_teardown()` (in module *nose2.tools.decorators*),  
    67